STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

DIVISION OF OIL, GAS AND MINING

	FORM 3
AMENDED R	REPORT
(highlight ch	anges)
	SURFACE:
062 St	ate
IN, ALLOTTEL ON THUS	
CA AGREEMENT NAME	
IAME and NUMBER:	
NZA 1023-20	
AND POOL, OR WILDC	AT:
TR, SECTION, TOWNS	HIP, RANGE,
IAN: 2 10S	23E
100	
TY: 13	3. STATE:
АН	UTAH
ACRES ASSIGNED TO	THIS WELL:
	80.00
RIPTION:	
238	<u>.</u>
DURATION:	
D SLURRY WEIGHT	
D OCOTACT VICEOUT	
···	
AND OTHER THAN THE	LEACE OWNED
ANY OTHER THAN THE	LEASE OWNER
 	

	APPLICATION FOR PERMIT TO DRILL						5. MINERAL LEASE NO: ML-47062	6. SURFACE: State
			REENTER [7. IF INDIAN, ALLOTTEE OF	TRIBE NAME:
1A. TYPE OF WOR			INCCIVICIN C.				8. UNIT or CA AGREEMENT	NAME:
B. TYPE OF WELL	.: OIL 🗌	gas 🗹	OTHER	SING	SLE ZONE MULTI	PLE ZONE 🗸		
2. NAME OF OPER		0.001404	ANV L D				9. WELL NAME and NUMBE BONANZA 1023	
WESTPORT 3. ADDRESS OF O		S COMPA	ANY L.P.		PHONE NUM		10. FIELD AND POOL, OR V	
1368 S 1200		CITY VER	NAL STA	TE UT ZIP 840	78 (435) 78	1-7024	BONANZA 11. QTR/QTR, SECTION, TO	OWNSHIP RANGE
4. LOCATION OF V			64592	1× 390	77216		MERIDIAN:	
AT SURFACE:	865'FSL &	1947'FEL	44259	64 Y -100	10128		SWSE 2 10	S 23E
AT PROPOSED	PRODUCING ZON	E:	()	, - 10	1. 0-1120			
14. DISTANCE IN	MILES AND DIREC	TION FROM N	EAREST TOWN OR PO	OST OFFICE:			12. COUNTY:	13. STATE: UTAH
			OURAY, UTAI				UINTAH	
15. DISTANCE TO					ACRES IN LEASE:	1	. NUMBER OF ACRES ASSIGNE	
865'						642.32	DOND DECORPTION	80.00
18. DISTANCE TO	NEAREST WELL) ON THIS LEASE	(DRILLING, CC (FEET)	MPLETED, OR	19. PROPOSED	DEPTH:		BOND DESCRIPTION:	
REFER TO	TOPO C	_			ATE DATE WORK WILL START		RLB0005238	· · · · · · · · · · · · · · · · · · ·
21. ELEVATIONS			ETC.):	22. APPROXIMA	ATE DATE WORK WILL STAR		. 20111011125	
5457';UNG	SRADED G	L						
24.			PROPOS	SED CASING A	ND CEMENTING PR	OGRAM		
SIZE OF HOLE	CASING SIZE.	GRADE, AND V	/EIGHT PER FOOT	SETTING DEPTH	CEME	NT TYPE, QUANTI	TY, YIELD, AND SLURRY WEIG	нт
12 1/4"	9 5/8"	H-40	32.3#	1,700	265 SX			
7 7/8"	4 1/2"	I-80	11.6#	8,300	1700 SX			•
1110	7 1/2							
				<u> </u>				
25.				ATTA	CHMENTS			
	LOWING ARE AT	TACHED IN AC	CORDANCE WITH THE	UTAH OIL AND GAS (CONSERVATION GENERAL RI	ULES:		
					1			
WELL PI	AT OR MAP PRE	PARED BY LICE	ENSED SURVEYOR OF	ENGINEER	COMPLETE DR			
V EVIDEN	CE OF DIVISION C	F WATER RIG	HTS APPROVAL FOR U	JSE OF WATER	FORM 5, IF OP	ERATOR IS PERS	ON OR COMPANY OTHER THA	N THE LEASE OWNER
		AUDOU	F00		REG	ULATORY	ANALYST	
NAME (PLEASE	PRINT) SHEII	LA UPCH	7 /		TITLE INCO			
SIGNATURE	Mush	2/1	nhun	2	DATE 4/16/	2004		
(This space for St	ate use only)		0					proved by the


API NUMBER ASSIGNED: 43-047-356 62

RECEIVED

APR 1 9 2004

Oil, Gas and Mining

(See Instructions on Reverse Side)



BONANZA #1023-20 SW/SE Sec. 2,T10S,R23E UINTAH COUNTY, UTAH ML-47062

ONSHORE ORDER NO. 1

DRILLING PROGRAM

1. Estimated Tops of Important Geologic Markers:

<u>Formation</u>	<u>Depth</u>
Uinta	Surface
Green River	1700'
Wasatch	4150'
Mesaverde	5950'
TD	8300'

2. Estimated Depths of Anticipated Water, Oil, Gas, or Mineral Formations:

Substance	<u>Formation</u>	<u>Depth</u>
Gas Gas	Green River Wasatch Mesaverde	1700' 4150' 5950'
Water Other Minerals	N/A N/A	

3. Pressure Control Equipment (Schematic Attached)

Please see the attached Drilling Program.

4. Proposed Casing & Cementing Program:

Please see the attached Drilling Program

5. Drilling Fluids Program:

Please see the attached Drilling Program.

6. <u>Evaluation Program</u>:

Please see the attached Drilling Program.

7. Abnormal Conditions:

Maximum anticipated bottomhole pressure calculated at 8300' TD, approximately equals 3320 psi (calculated at 0.4 psi/foot).

Maximum anticipated surface pressure equals approximately 1494 psi (bottomhole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

8. Anticipated Starting Dates:

Drilling is planned to commence immediately upon approval of this application.

9. <u>Variances:</u>

Please see the attached Drilling Program.


10. Other Information:

Please see the attached Drilling Program.



Westport Oil and Gas Company, L.P. DRILLING PROGRAM

COMPANY N	AME	Westport Oil and Gas Co., L.P.	DATE	April 16,	16, 2004		
WELL NAME		BONANZA 1023-20	TD	8,300'	MD/TVD		
FIELD B	onanza	COUNTY Uintah STATE	Utah ELEV	ATION	5,456' GL	KE	3 5,471'
SURFACE LO	CATION	865' FSL & 1947' FEL, SWSE Sec. 2	T 10S R 23E			BHL	Straight Hole
		Latitude: 39.973031 Longitude: 10	9.291819				
OBJECTIVE :	ZONE(S)	Wasatch/Mesaverde					
ADDITIONAL	INFO	Regulatory Agencies: UDOGM (SURFACE	& MINERALS), Tri-	-County He	ealth Dept.		





CASI	NG	PRC	GR	ΔМ

CACINOTINOS								DESIGN FACTORS			
	SIZE	IN	TERV	AL	WT.	GR.	CPLG.	BURST	COLLAPSE	TENSION	
CONDUCTOR SURFACE PRODUCTION	14" 9-5/8" 4-1/2"	0	0-40' to to	1700 8300	32.30 11.60	H-40 M-80 or 1-80	STC	2270 0.91******* 7780 3.12	1370 1.72 6350 1.47	254000 5.28 201000 2.39	
		1					<u> </u>	L	<u> </u>		

- 1) Max Anticipated Surf. Press.(MASP) (Surface Casing) = (Pore Pressure at next csg point-(0.22 psi/ft-partial evac gradient x TVD of next csg point)
- 2) MASP (Prod Casing) = Pore Pressure at TD (.22 psi/ft-partial evac gradient x TD)

(Burst Assumptions: TD =

10.0 ppg)

.22 psi/ft = gradient for partially evac wellbore

(Collapse Assumption: Fully Evacuated Casing, Max MW)

(Tension Assumptions: Air Weight of Casing*Buoy.Fact. of water)

2490 psi MASP

Burst SF is low but csg is much stronger than formation at 2000'. EMW @ 2000' for 2270# is 21.8 ppg or 1.13 psi/ft

CEMENT PROGRAM

	Ī	FT. OF FILL	DESCRIPTION	SACKS	EXCESS	WEIGHT	YIELD
SURFACE	LEAD	500	Premium cmt + 2% CaCl	215	60%	15.60	1.18
Option 1			+ .25 pps flocele				ļ
Op	TOP OUT CMT (1)	200	20 gals sodium silicate + Premium cmt	50		15.60	1.18
			+ 2% CaCl + .25 pps flocele				
	TOP OUT CMT (2)	as required	Premium cmt + 2% CaCl	as req.		15.60	1.18
SURFACE			NOTE: If well will circulate water to s	urface, opt	ion 2 will b		
Option 2	LEAD	1500	Prem cmt + 16% Gel + 10 pps gilsonite	170	35%	11.00	3.82
-			+.25 pps Flocele + 3% salt BWOC		'		
	TAIL	500	Premium cmt + 2% CaCl	180	35%	15.60	1.18
			+ .25 pps flocele	1			
	TOP OUT CMT	as required	Premium cmt + 2% CaCl	as req.		15.60	1.18
PRODUCTIO	N LEAD	3,650'	Premium Lite II + 3% KCl + 0.25 pps	400	60%	11.00	3.38
1110000111			celloflake + 5 pps gilsonite + 10% gel				
			+ 0.5% extender				i
	TAIL	4,650'	50/50 Poz/G + 10% salt + 2% gel	1300	60%	14.30	1.31
			+.1% R-3		L		

^{*}Substitute caliper hole volume plus 0% excess for LEAD if accurate caliper is obtained

FLOAT EQUIPMENT & CENTRALIZERS

SURFACE	Guide shoe, 1 jt, insert float. Centralize first 3 joints with bow spring centralizers. Thread lock guide shoe.	
PRODUCTION	Float shoe, 1 jt, float collar. Centralize first 3 joints & every third joint to top of tail cement with bow spring centralizers.	

ADDITIONAL INFORMATION

	Test casing head to 750 psi aft	r installing. Test surface casing to 1,500 psi prior to drilling out.	
	BOPE: 11" 3M with one annula	r and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Rec	cord on chart recorder &
	tour sheet. Function test rams	on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kell	y to be equipped with upper
	& lower kelly valves.		
	Drop Totco surveys every 2000	Maximum allowable hole angle is 5 degrees.	
		D	DATE:
DRILLING	ENGINEER:	Brad Laney	
DRILLING	SUPERINTENDENT:		DATE:

DHD_BON1023-2O_APD

Randy Bayne

^{*}Substitute caliper hole volume plus 15% excess for TAIL if accurate caliper is obtained

BONANZA #1023-20 SW/SE Sec. 2, T10S-R23E Uintah County, UT ML-47062

ONSHORE ORDER NO. 1

MULTI-POINT SURFACE USE & OPERATIONS PLAN

1. Existing Roads:

Refer to Topo Map A for directions to the location.

Refer to Topo Maps A and B for location of access roads within a 2-mile radius.

Refer to Topo Maps A and B for location of access roads within a 2 mile radius.

Improvements to existing access roads shall be determined at the on-site inspection.

All existing roads will be maintained and kept in good repair during all drilling and completion operations associated with this well.

2. Planned Access Roads:

Refer to Topo Map B for the location of the proposed access road.

The upgraded and new portions of the access road will be crowned and ditched with a running surface of 18 feet and a maximum disturbed width of 30 feet, *unless modified at the on-site inspection*. Appropriate water control will be installed to control erosion.

Existence of pipelines; maximum grade; turnouts; major cut and fills, culverts, or bridges; gates, cattle guards, fence cuts, or modifications to existing facilities shall be determined at the on-site.

The access road was centerline flagged during time of staking.

Surfacing material may be necessary, depending upon weather conditions.

Surface disturbance and vehicular traffic will be limited to the approved location and approved access route. Any additional area needed will be approved in advance.

3. <u>Location of Existing Wells Within a 1-Mile Radius</u>:

Please refer to Topo Map C.

4. <u>Location of Existing & Proposed Facilities</u>:

The following guidelines will apply if the well is productive.

All production facilities will be located on the disturbed portion of the well pad and at a minimum of 25 feet from the toe of the back slope or the top of the fill slope.

A dike will be constructed completely around those production facilities which contain fluids (i.e., production tanks, produced water tanks, and/or heater/treater). These dikes will be constructed of compacted subsoil, be impervious, hold 100% of the capacity of the largest tank, and be independent of the back cut.

All permanent (on-site six months or longer) above the ground structures constructed or installed, including pumping units, will be painted a flat, non-reflective, earthtone color to match one of the standard environmental colors, as determined by the five state Rocky Mountain Inter-Agency Committee.

All facilities will be painted within six months of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) will be excluded. The required color is Carlsbad Canyon, standard color number 2.5Y 6/2.

Any necessary pits will be properly fenced to protect livestock and prevent wildlife entry.

Refer to Topo D for the proposed pipeline.

5. Location and Type of Water Supply:

Water for drilling purposes will be obtained from Dalbo Inc.'s underground well located in Ouray, Utah, Sec. 32, T4S, R3E, Water User Claim #43-8496, Application #53617.

Water will be hauled to location over the roads marked on Maps A and B.

No water well is to be drilled on this lease.

6. Source of Construction Materials:

Surface and subsoil materials in the immediate area will be utilized.

Any gravel will be obtained from a commercial source.

7. Methods of Handling Waste Materials:

Drill cuttings will be contained and buried in the reserve pit.

Drilling fluids, including salts and chemicals, will be contained in the reserve pit. Upon termination of drilling and completion operations, the liquid contents of the reserve pit will be removed and disposed of at an approved waste disposal facility within 120 days after drilling is terminated.

The reserve pit will be constructed on the location and will not be located within natural drainage, where a flood hazard exists or surface runoff will destroy or damage the pit walls. The reserve pit will be constructed so that it will not leak, break, or allow discharge of liquids. The need for a reserve pit liner will be determined at the on-site inspection.

If a plastic reinforced liner is used, it will be a minimum of 12 mil thick, with sufficient bedding used to cover any rocks. The liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash or scrap that could puncture the liner will be disposed of in the pit.

Any spills of oil, gas, salt water, or other noxious fluids will be immediately cleaned up and removed to an approved disposal site.

A chemical porta-toilet will be furnished with the drilling rig.

Garbage, trash, and other waste materials will be collected in a portable, self-contained, fully enclosed trash cage during operations. No trash will be burned on location.

All debris and other waste material not contained in the trash cage will be cleaned up and removed from the location immediately after removal of the drilling rig.

Any open pits will be fenced during the operations. The fencing will be maintained until such time as the pits are backfilled.

No chemicals subject to reporting under SARA Title III (hazardous materials) in an amount greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling of this well.

Any produced water from the proposed well will be contained in a water tank and will then be hauled By truck to one of the pre-approved disposal sites: RNI, Sec. 5, T9S, R22E, NBU #159, Sec. 35, T9S, R21E, Ace Oilfield, Sec. 2, T6S, R20E, MC&MC, Sec. 12, T6S, R19E.

8. Ancillary Facilities:

None are anticipated.

9. Well Site Layout: (See Location Layout Diagram)

The attached Location Layout Diagram describes drill pad cross-sections, cuts and fills, and locations of the mud tanks, reserve pit, flare pit, pipe racks, trailer parking, spoil dirt stockpile(s), and surface material stockpile(s). *This section is subject to modification as a result of the on-site inspection*.

Please see the attached diagram to describe rig orientation, parking areas, and access roads.

If it is determined that a pit liner will be used at the on-site inspection, the reserve pit will be lined, and when the reserve pit is closed, the pit liner will be buried below plow depth.

All pits will be fenced according to the following minimum standards:

39 inch net wire will be used with at least one strand of barbed wire on top of the net wire. Barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence.

The net wire shall be no more than two inches above the ground. The barbed wire shall be three inches over the net wire. Total height of the fence shall be at least 42 inches.

Corner posts shall be cemented and/or braced in such a manner to keep the fence tight at all times.

Standard steel, wood, or pipe posts shall be used between the corner braces. Maximum distance between any 2 fence posts shall be no greater than 16 feet.

All wire shall be stretched, by using a stretching device, before it is attached to corner posts.

The reserve pit fencing will be on three sides during drilling operations, and on the fourth side when the rig moves off location. Pits will be fenced and maintained until cleanup.

Location size may change prior to the drilling of the well due to current rig availability. If the proposed location is not large enough to accommodate the drilling rig the location will be re-surveyed and a Form 9 shall be submitted.

10. Plans for Reclamation of the Surface:

Producing Location:

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, materials, trash, and debris not required for production.

Immediately upon well completion, any hydrocarbons in the pit shall be removed in accordance with 43 CFR 3162.7-1.

If a plastic, nylon reinforced liner is used, it shall be torn and perforated before backfilling of the reserve pit.

Before any dirt work associated with location restoration takes place, the reserve pit shall be as dry as possible. All debris in it will be removed. Other waste and spoil materials will be disposed of immediately upon completion of operations.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximate natural contours. The reserve pit will be reclaimed within 90 days from the date of well completion, weather permitting.

To prevent surface water (s) from standing (ponding) on the reclaimed reserve pit area, final reclamation of the reserve pit will consist of "mounding" the surface three feet above surrounding ground surface to allow the reclaimed pit area to drain effectively.

Upon completion of backfilling, leveling, and recontouring, the stockpiled topsoil will be spread evenly over the reclaimed area(s).

Dry Hole/Abandoned Location:

Abandoned well sites, roads, and other disturbed areas will be restored as near as practical to their original condition. Where applicable, these conditions include the re-establishment of irrigation systems, the re-establishment of appropriate soil conditions, and re-establishment of vegetation as specified.

All disturbed surfaces will be recontoured to the approximate natural contours, with reclamation of the well pad and access road to be performed as soon as practical after final abandonment. Reseeding operations will be performed after completion of other reclamation operations.

11. <u>Surface Ownership</u>:

SITLA 675 East 500 South, Suite 500 Salt Lake City, UT 84102

12. Other Information:

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, the approved Plan of Operations, and any applicable Notice of Lessees. The Operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished to the field representative to ensure compliance.

The Operator will control noxious weeds along Rights-Of-Way for roads, pipelines, well sites, or other applicable facilities.

A Class III archaeological survey has been completed and a copy of this report will be submitted when it becomes available.

13. Lessee's or Operators's Representative & Certification:

Sheila Upchego Regulatory Analyst Westport O&G Co. L.P. P.O. Box 1148 Vernal, UT 84078 (435) 781-7024 Randy Bayne Drilling Manager Westport O&G Co. L.P. P.O. Box 1148 Vernal, UT 84078 (435) 781-7018

Certification: All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved Plan of Operations, and any applicable Notice to Lessees.

The Operator will be fully responsible for the actions of its subcontractors. A complete copy of the approved "Application for Permit to Drill" will be furnished to the field representative(s) to ensure compliance and shall be on location during all construction and drilling operations.

Westport O& GCo. L.P. is considered to be the operator of the subject well. Westport O& G Co. L.P agrees to be responsible under terms and conditions of the lease for the operations conducted upon leased lands.

Bond coverage pursuant to 43 CFR 3104 for lease activities is being provided by Westport O&G Co. L.P. State Surety Bond: RLB0005.

I hereby certify that I, or persons under my supervision, have inspected the proposed drill site and access route, that I am familiar with the conditions that currently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and the work associated with the operations proposed herein will be performed by the Operator, its contractors, and subcontractors in conformity with this plan and the terms and conditions under which it is approved.


Sheila Upchego


A/16/04
Date

WESTPORT OIL AND GAS COMPANY, L.P. BONANZA #1023-20 SECTION 2, T10S, R23E, S.L.B.&M.


PROCEED IN A WESTERLY DIRECTION FROM VERNAL, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 14.0 MILES TO THE JUNCTION OF STATE HIGHWAY 88; EXIT LEFT AND PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 17.0 MILES TO OURAY, UTAH; PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 0.3 MILES ON THE SEEP RIDGE ROAD TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE EAST; TURN LEFT AND PROCEED IN AN EASTERLY DIRECTION APPROXIMATELY 12.3 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTH; TURN RIGHT AND PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 1.7 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE TURN LEFT AND PROCEED IN AN EASTERLY DIRECTION APPROXIMATELY 1.9 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHEAST; TURN RIGHT AND PROCEED IN A SOUTHEASTERLY DIRECTION APPROXIMATELY 0.5 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE EAST; TURN LEFT AND PROCEED IN AN EASTERLY, THEN SOUTHEASTERLY DIRECTION APPROXIMATELY 3.3 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHWEST; TURN RIGHT AND PROCEED IN A SOUTHWESTERLY DIRECTION APPROXIMATELY 0.7 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTH; TURN LEFT AND PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 5.1 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTHEAST; TURN LEFT AND PROCEED IN A NORTHEASTERLY, THEN EASTERLY DIRECTION APPROXIMATELY 5.1 MILES TO THE BEGINNING OF THE PROPOSED ACCESS TO THE NORTHWEST; FOLLOW ROAD FLAGS IN A NORTHWESTERLY DIRECTION APPROXIMATELY 0.2 MILES TO THE PROPOSED LOCATION.


TOTAL DISTANCE FROM VERNAL, UTAH TO THE PROPOSED WELL LOCATION IS APPROXIMATELY 62.1 MILES.






EOP STACK







WESTPORT OIL AND GAS COMPANY, L.P.

BONANZA #1023-20

LOCATED IN UINTAH COUNTY, UTAH SECTION 2, T10S, R23E, S.L.B.&M.




PHOTO: VIEW FROM CORNER #5 TO LOCATION STAKE

CAMERA ANGLE: SOUTHERLY



PHOTO: VIEW FROM BEGINNING OF PROPOSED ACCESS

CAMERA ANGLE: NORTHERLY




Uintah Engineering & Land Surveying S South 200 East Vernal, Utah 84078 435-789-1017 vels@uelsinc.com


LOCATION PHOTOS


MONTH DAY YEAR

РНОТО

TAKEN BY: S.H. DRAWN BY: T.H. REVISED: 00-00-00








workshi	~	-			
APD RECEIVED: 04/19/2004	API NO. ASSIGN	ED: 43-047-356	62		
WELL NAME: BONANZA 1023-20 OPERATOR: WESTPORT OIL & GAS CO (N2115) CONTACT: SHEILA UPCHEGO PROPOSED LOCATION:	phone number: 435-781-7024				
SWSE 02 100S 230E	INSPECT LOCATI	N BY: /	/		
SURFACE: 0865 FSL 1947 FEL	Tech Review	Initials	Date		
BOTTOM: 0865 FSL 1947 FEL UINTAH	Engineering	DKO	5/21/04		
NATURAL BUTTES (630)	Geology				
LEASE TYPE: 3 - State LEASE NUMBER: ML-47062	Surface				
SURFACE OWNER: 3 - State PROPOSED FORMATION: MVRD COALBED METHANE WELL? NO	LATITUDE: 39.9 LONGITUDE: 109	97316 .29128			
RECEIVED AND/OR REVIEWED:	LOCATION AND SIT	ring:			
Plat Bond: Fed[] Ind[] Sta[3] Fee[]	R649-2-3.				
(No. RLB0005238 eV) N Potash (Y/N) N Oil Shale 190-5 (B) or 190-3 or 190-13 Water Permit (No. 43-8496)	Unit R649-3-2. Siting: 460 R649-3-3. Drilling Un	From Qtr/Qtr & 920 Exception	' Between Wells		
N RDCC Review (Y/N) (Date:) N Fee Surf Agreement (Y/N)	Board Caus Eff Date: Siting: 40	se No: /79-	999 £ 920 fr other Will		

COMMENTS:	Need (Prin (05-06-02)	
STIPULATIONS:	O STATEMENT OF RASIS	



From:

Ed Bonner

To:

Whitney, Diana

Date:

4/23/2004 12:44:52 PM

Subject:

Well Clearance

The following wells have been given cultural resource clearance by the Trust Lands Cultural Resources Group:

MSC Exploration State MSC 16-1

Miller, Dyer & Company Ute Tribal 10-2-15-20

Westport Oil & Gas Company Bonanza 1023-2G Bonanza 1023-2I Bonanza 1023-2O

ConocoPhillips Company Utah 32-617

If you have any questions regarding this matter please give me a call.

CC:

Garrison, LaVonne; Hill, Brad; Hunt, Gil

ON-SITE PREDRILL EVALUATION Division of Oil, Gas and Mining

OPERATOR: WESTORT OIL AND GAS COMPANY, L.P.

WELL NAME & NUMBER: BONANZA 1023-20

API NUMBER: 43-047-35662

LEASE: ML-47062 FIELD/UNIT: NATURAL BUTTES

LOCATION: 1/4,1/4 SW/SE Sec: 2 TWP: 10S RNG: 23E 1947' FEL 865' FSL LEGAL WELL SITING: 460' from unit boundary and 920' from another well.

GPS COORD (UTM): 645936E 4425959N SURFACE OWNER: STATE OF UTAH

PARTICIPANTS

DAVID W. HACKFORD (DOGM), FLOYD BARTLETT (DWR), CARROLL ESTES, CLAY EINERSON, (WESTPORT), DAVID WESTON, (UELS).

REGIONAL/LOCAL SETTING & TOPOGRAPHY

SITE IS IN A RELATIVELY FLAT AREA WHICH DRAINS SLIGHTLY TO THE SOUTHEAST. THE WHITE RIVER 1.4 MILES TO THE SOUTHEAST. THERE IS A ROCKY RIDGE RUNNING EAST TO WEST 700' NORTH OF SITE. OURAY, UTAH IS 31.1 MILES TO THE NORTHWEST. BONANZA, UTAH IS SIX MILES TO THE EAST.

SURFACE USE PLAN

CURRENT SURFACE USE: WILDLIFE AND LIVESTOCK GRAZING, HUNTING.

PROPOSED SURFACE DISTURBANCE: LOCATION WILL BE 350' BY 273'. ACCESS ROAD WILL BE 0.2 MILES.

LOCATION OF EXISTING WELLS WITHIN A 1 MILE RADIUS: SEE ATTACHED MAP FROM GIS DATABASE.

LOCATION OF PRODUCTION FACILITIES AND PIPELINES: ALL PRODUCTION FACILITIES WILL BE ON LOCATION AND ADDED AFTER DRILLING WELL. AN EXISTING PIPELINE IS ADJACENT TO SITE.

SOURCE OF CONSTRUCTION MATERIAL: ALL CONSTRUCTION MATERIAL WILL BE BORROWED FROM SITE DURING CONSTRUCTION OF LOCATION.

ANCILLARY FACILITIES: NONE WILL BE REQUIRED.

WASTE MANAGEMENT PLAN:

DRILLED CUTTINGS WILL BE SETTLED INTO RESERVE PIT. LIQUIDS FROM PIT WILL BE ALLOWED TO EVAPORATE. FORMATION WATER WILL BE CONFINED TO STORAGE TANKS. SEWAGE FACILITIES, STORAGE AND DISPOSAL WILL BE HANDLED BY COMMERCIAL CONTRACTOR. TRASH WILL BE CONTAINED IN TRASH BASKETS AND HAULED TO AN APPROVED LAND FILL.

ENVIRONMENTAL PARAMETERS

AFFECTED FLOODPLAINS AND/OR WETLANDS: NONE

FLORA/FAUNA: SAGE, GREASEWOOD, HORSEBRUSH, PRICKLY PEAR, SHADSCALE,

CHEATGRASS: PRONGHORN, RODENTS, SONGBIRDS, RAPTORS, COYOTE, RABBITS. SOIL TYPE AND CHARACTERISTICS: LIGHT BROWN SANDY CLAY. VERY LITTLE NATURAL EROSION. EROSION/SEDIMENTATION/STABILITY: SEDIMENTATION AND STABILITY ARE NOT A PROBLEM AND LOCATION CONSTRUCTION SHOULDN'T CAUSE AN INCREASE IN STABILITY OR EROSION PROBLEMS. PALEONTOLOGICAL POTENTIAL: NONE OBSERVED. RESERVE PIT CHARACTERISTICS: 150' BY 100' AND 10' DEEP. LINER REQUIREMENTS (Site Ranking Form attached): A LINER WILL NOT BE REQUIRED FOR RESERVE PIT. SURFACE RESTORATION/RECLAMATION PLAN AS PER SITLA. SURFACE AGREEMENT: AS PER SITLA. CULTURAL RESOURCES/ARCHAEOLOGY: SITE WAS INSPECTED BY MONTGOMERY ARCHEOLOGICAL CONSULTANTS. A REPORT OF THIS INVESTIGATION WILL BE PLACED ON FILE. OTHER OBSERVATIONS/COMMENTS

THIS PREDRILL INVESTIGATION WAS CONDUCTED ON A WARM DAY WITH NO SNOW COVER.

ATTACHMENTS

PHOTOS OF THIS SITE WERE TAKEN AND PLACED ON FILE.

DAVID W. HACKFORD DOGM REPRESENTATIVE 5/06/04, 11:00 AM DATE/TIME

Evaluation Ranking Criteria and Ranking Store For Reserve and Onsite Pit Liner Requirements

Site-Specific Factors	Ranking	Site Ranking
	· · · · · · · · · · · · · · · · · · ·	
Distance to Groundwater (feet) >200	0	
100 to 200 75 to 100	5 10	
25 to 75	15	0
<25 or recharge area	20	0
Distance to Surf. Water (feet)	0	
>1000 300 to 1000	2	
200 to 300	10 15	
100 to 200 < 100	20	0
Distance to Nearest Municipal		
Well (feet)	0	
>5280 1320 to 5280	5	
500 to 1320	10	0
<500	20	
Distance to Other Wells (feet) >1320	0	
300 to 1320	10	0
<300	20	
Native Soil Type	0	
Low permeability Mod. permeability	10	
High permeability	20	<u>10</u>
Fluid Type	0	
Air/mist Fresh Water	5	
TDS >5000 and <10000	10	
TDS >10000 or Oil Base Mud Fluid containing significant levels of	15	
hazardous constituents	20	5
Drill Cuttings	0	
Normal Rock Salt or detrimental	0 10	0
Annual Precipitation (inches) <10	0	
10 to 20	5	0
>20	10	
Affected Populations <10	0	
10 to 30	6	
30 to 50	8 10	0
>50	20	
Presence of Nearby Utility Conduits		
Not Present	0	
Unknown Present	10 15	0
riesenc		


15 (Level II Sensitivity)


Sensitivity Level I = 20 or more; total containment is required.

Sensitivity Level II = 15-19; lining is discretionary.

Sensitivity Level III = below 15; no specific lining is required.

Final Score






DIVISION OF OIL, GAS AND MINING APPLICATION FOR PERMIT TO DRILL STATEMENT OF BASIS

OPERATOR:	WESTPORT OIL AND GAS C	COMPANY, L.P.
WELL NAME & NUMBER:		
API NUMBER:	43-047-35662	
LOCATION: 1/4,1/4 <u>SW/SE</u> Sec:	2 TWP: 10S RNG: 23E 194	<u>.7'</u> FEL <u>865'</u> FSL
Geology/Ground Water:		
saline water at this location is estimated shows no water wells within a 10,00 the Uinta Formation. The Uinta Formation are mostly lenticular and discontinuous	ated to be at a depth of 3,450. A of foot radius of the proposed locarmation is made up of interbedded and should not be a signification brought to above the base of the	the depth to the base of the moderately search of Division of Water Rights records cation. The surface formation at this site is ed shales and sandstones. The sandstones and source of useable ground water. e moderately saline groundwater in order to
Reviewer:		
Surface:		
with SITLA were invited to this invented to the construction of this location or tappears to be the best site for a local supersonable size of this size.	stigation on 04/28/04. Mr. Bartle he drilling of the well. This site tion in the immediate area. Cart section, and Montgomery Archeo belines were being surveyed. Mr.	A. Floyd Bartlett with DWR and Ed Bonner ett was present. He had no concerns regarding is on State surface, with State minerals, and roll Estes with Westport stated that that there blogical Consultants would work closely with Bartlett gave Mr. Estes a prescribed seed mix
Reviewer: <u>David V</u>	V. Hackford Da	te: <u>05/07/2004</u>
Conditions of Approval/Applicat	ion for Permit to Drill:	

None.

Casing Schematic



Well name:

05-04 Westport 1023-20

Operator:

Westport Oil & Gas Company

String type:

Surface

Project ID: 43-047-35662

Location:

Uintah County

Injection pressure

Design parameters: <u>Collapse</u> Mud weight: Design is based on evacuated pipe.		Minimum design f Collapse: Design factor	1.125	Environment: H2S considered? Surface temperature: Bottom hole temperature: Temperature gradient: Minimum section length:	No 65 °F 89 °F 1.40 °F/100ft 200 ft
		Burst: Design factor	1.00	Cement top:	341 ft
Burst Max anticipated surface pressure: Internal gradient: Calculated BHP No backup mud specified.	431 psi 0.468 psi/ft 1,226 psi	Tension: 8 Round STC: 8 Round LTC: Buttress: Premium:	1.80 (J) 1.80 (J) 1.60 (J) 1.50 (J)	Non-directional string.	
		Body yield: Tension is based on Neutral point:	1.50 (B)	Re subsequent strings: Next setting depth: Next mud weight: Next setting BHP: Fracture mud wt: Fracture depth:	8,300 ft 10.000 ppg 4,312 psi 19.250 ppg 1,700 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	1700	9.625	32.30	H-40 -	ST&C	1700	1700	8.876	107.7
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor 4.63 J
1	742	1370	1.847~	1226	2270	1.85 —	55	254	4.03 J

Prepared

Clinton Dworshak

Utah Div. of Oil & Mining

Phone: 801-538-5281 FAX: 801-359-3940

Date: May 18,2004 Salt Lake City, Utah

1,700 psi

Collapse is based on a vertical depth of 1700 ft, a mud weight of 8.4 ppg The casing is considered to be evacuated for collapse purposes. Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Well name:

05-04 Westport 1023-20

Operator:

Westport Oil & Gas Company

String type:

Production

Location:

Uintah County

Project ID:

43-047-35662

Environment:

Design parameters:

Collapse

Mud weight:

10.000 ppg Design is based on evacuated pipe.

Minimum design factors:

Collapse:

1.125 Design factor

H2S considered? Surface temperature: No 65 °F

Bottom hole temperature: Temperature gradient:

181 °F 1.40 °F/100ft

Minimum section length: 368 ft

Burst:

Design factor

1.00

1.80 (J)

1.80 (J)

Cement top:

Surface

Burst

Max anticipated surface

pressure: Internal gradient:

431 psi 0.468 psi/ft 4.311 psi

Calculated BHP

No backup mud specified.

Tension:

8 Round STC: 8 Round LTC:

1.60 (J) **Buttress:** 1.50 (J) Premium: 1.50 (B) Body yield:

Tension is based on air weight. 7,059 ft Neutral point:

Non-directional string.

Run Seq	Segment Length (ft) 8300 ~	Size (in) 4.5	Nominal Weight (lbs/ft) 11.60	Grade M-80 ~	End Finish LT&C	True Vert Depth (ft) 8300	Measured Depth (ft) 8300	Drift Diameter (in) 3.875	Internal Capacity (ft³) 192.4
Run Seq	Collapse Load (psi) 4311	Collapse Strength (psi) 6350	Collapse Design Factor 1.473	Burst Load (psi) 4311	Burst Strength (psi) 7780	Burst Design Factor 1.80	Tension Load (Kips) 96	Tension Strength (Kips) 267	Tension Design Factor 2.77 B

Prepared

Clinton Dworshak

Utah Div. of Oil & Mining

Phone: 801-538-5281 FAX: 801-359-3940

Date: May 18,2004 Salt Lake City, Utah

Collapse is based on a vertical depth of 8300 ft, a mud weight of 10 ppg. The casing is considered to be evacuated for collapse purposes. Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.



State of Utah

Department of Natural Resources

ROBERT L. MORGAN Executive Director

Division of Oil, Gas & Mining

LOWELL P. BRAXTON
Division Director

OLENE S. WALKER

Governor

GAYLE F. McKEACHNIE
Lieutenant Governor

May 24, 2004

Westport Oil & Gas Company L.P. 1368 South 1200 East Vernal, UT 84078

Re:

Bonanza 1023-20 Well, 865' FSL, 1947' FEL, SW SE, Sec. 2, T. 10 South,

R. 23 East, Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann.§ 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-35662.

Sincerely,

John R. Baza
Associate Director

pab Enclosures

cc:

Uintah County Assessor

SITLA



Operator:	Westport Oil & Gas Company L.P.					
Well Name & Number	Bonanza 1023-2O					
API Number:	43-047-35662					
Lease:	ML-47	<u> </u>				
Location: SW SE	Sec. 2	T. 10 South	R. 23 East			

Conditions of Approval

1. General

Location: SW SE

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Notification Requirements 2.

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

- 24 hours prior to cementing or testing casing
- 24 hours prior to testing blowout prevention equipment

Sec. 2

- 24 hours prior to spudding the well
- within 24 hours of any emergency changes made to the approved drilling program
- prior to commencing operations to plug and abandon the well

The following are Division of Oil, Gas and Mining contacts and their work telephone numbers (please leave a voice mail message if the person is not available to take the call):

- Dan Jarvis at (801) 538-5338
- Carol Daniels at (801) 538-5284 (spud)

Reporting Requirements 3.

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

- Compliance with the State of Utah Antiquities Act forbids disturbance of archeological, 4. historical, or paleontological remains. Should archeological, historical or paleontological remains be encountered during your operations, you are required to immediately suspend all operations and immediately inform the Trust Lands Administration and the Division of State History of the discovery of such remains.
- Compliance with the Conditions of Approval/Application for Permit to Drill outlined in 5. the Statement of Basis. (Copy Attached)

STATE OF UTAH DIVISION OF OIL, GAS AND MINING ENTITY ACTION FORM-FORMS

9 ۵.

AUG-30-2004 MON 08:30 AM

OPERATOR WESTPORT O & G COMPANY, L.P. **ADDRESS** 1368 SOUTH 1200 EAST **VERNAL, UT 84078**

٠,	ACTION	CURRENT	NEW	API NUMBER	WELL NAME			MEIT IC	CATION		SPUD	BFFECTIVE	
۵.	CODE	ENTITY NO.	ENTITY NO.			QQ	SC	TP	RG	COUNTY	DATE	DATE	i
		99999	14289	43-047-35662	BONANZA 1023-20	SWSB	2	105	23E	UINTAH	8/27/2004	8/31/04	K
)	WELL 1 CC	HAMENTS:	m	URD									l
		MARTIN RA	THOLE									1	
				@ 2330 HOURS				AAFT LL L	OO L TION		- ADM D	EFFECTIVE	l
!	ACTION	CURRENT	NEW	API NUMBER	WELL NAME	aq	SC	TP	OCATION RG	COUNTY	SPUD DATE	DATE	1
	CODE	ENTITY NO.	ENTITY NO.			uu	30	l Ir	110	COONT	- MIL	1 /	11
4357817094		99999	14290	43-047-35663	BONANZA 1023-21	NWSE	2	108	23E	UINTAH	8/26/2004	8/31/04	K
		DAMENTS:		MURD									
21		MARTIN RA	THOLE	•	_								l
43				4 @ 1600 HOUR	S WELL NAME			WEILE	OCATION		SPUD	EFFECTIVE	ŧ
	ACTION	CURRENT ENTITY NO.	NEW Entity No.	API NUMBER	TYCLL IVANIC	QQ	SC	TP	RG	COUNTY	DATE	DATE	
≥,	LULE .	ENTITINO.						1	1			0/1	11
EC.		99999	14291	43-047-35661	BONANZA-1023-2G	SWNE	2	105	₽3E	UINTAL	8/26/2004	131/04	K
<u>. </u>	WELL 3 C	OMMENTS:	17.5011		n VRD			* * * * * * * * * * * * * * * * * * * *					İ
		MARTIN RA	THOLE	7	NVAD								ł
			ON ON 8-26-0	4@11:30 AM									j
	ACTION	CURRENT	NEW	API NUMBER	WELL NAME		1		OCATION	I commen	SPUC	EFFECTIVE DATE	
	CODE	ENTITY NO.	ENTITY NO.			QQ	SC	TP	RG	COUNTY	OATE	LAIE	1
PASO PRODUCTION		ļ		,									
5	WELL 4 C	OMMENTS:		ſ					•				i
Ž				l	Post-it® Fax Note 7671	teV_20.14	ë of ▶ pages	T					1
2						<u> </u>					T	T	4
<u> </u>	ACTION	CURRENT	NEW	API NUMB	Farun Russell	Acres	NW	idale	CATION	COLNEY	SPUD DATE	EFFECTIVE DATE	1
8	CODE	ENTITY NO.	ENTITY NO.		Co/Dept NYCOM	. West-pa	Y. F		RG	COUNTY	LIAIE	UNIE	1
<u>R</u>	`			'	Phone #201-530. (22)	one# 425-	187	70214			1	1	1
딥	/	OLD FATO:	<u> </u>		- 1 (O) E	WI UDB-130							1
	WELL 5 C	OMMENTS:			Fax 801-359-3947)	435.1	81-16	29_					
Æ													1
08:30	105/01/6	opro (o	-decellene ee bee	t of form)						$\overline{}$			_
<u>~</u>			structions on bac							X allon	ر (ا ا ،	dalla.	
				il (single well only)					ش	Signature		WILL	-
MON				group or unit well)	wisting onlike					- Barrer A			
 				g entity to anothe r e						REGULATO	RY ADMIN	08/30/04	
30-2004				g entity to a new en	w y	חבו	CEIV	ED		Title	and the party.	Date	-
7			in comments sec		tada uma galastad	חבו	۷۱۱۷	בט					
-30 -30	NOTE: U:	SE CUMINICNI S	section to explain	why each Action C	ons May 2016Cign	ΔUG	302	1114		Phone No.	435-7	81-7044	_

FORM 9 STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES 5. LEASE DESIGNATION AND SERIAL NUMBER: DIVISION OF OIL, GAS AND MINING 006 ML-47062 6. IF INDIAN, ALLOTTEE OR TRIBE NAME: SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT or CA AGREEMENT NAME: Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals. 8. WELL NAME and NUMBER: 1. TYPE OF WELL GAS WELL 🗸 OTHER OIL WELL . **BONANZA 1023-20** 9. API NUMBER: 2. NAME OF OPERATOR 4304735662 WESTPORT OIL & GAS COMPANY L.P. 10. FIELD AND POOL, OR WILDCAT: PHONE NUMBER: 3. ADDRESS OF OPERATOR **NATURAL BUTTES** (435) 781-7024 UT 712 84078 **VERNAL** 1368 S 1200 E 4. LOCATION OF WELL COUNTY: UINTAH FOOTAGES AT SURFACE: 865'FSL & 1947'FEL STATE: 10S 23E QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: SWSE 2 **UTAH** CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 11. TYPE OF ACTION TYPE OF SUBMISSION REPERFORATE CURRENT FORMATION DEEPEN **ACIDIZE** NOTICE OF INTENT SIDETRACK TO REPAIR WELL FRACTURE TREAT ALTER CASING (Submit in Duplicate) TEMPORARILY ABANDON NEW CONSTRUCTION CASING REPAIR Approximate date work will start TUBING REPAIR OPERATOR CHANGE CHANGE TO PREVIOUS PLANS VENT OR FLARE PLUG AND ABANDON CHANGE TUBING WATER DISPOSAL PLUG BACK SUBSEQUENT REPORT CHANGE WELL NAME (Submit Original Form Only) WATER SHUT-OFF PRODUCTION (START/RESUME) CHANGE WELL STATUS Date of work completion: OTHER: WELL SPUD RECLAMATION OF WELL SITE COMMINGLE PRODUCING FORMATIONS 9/27/2004 RECOMPLETE - DIFFERENT FORMATION CONVERT WELL TYPE 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. MIRU PETE MARTIN BUCKET RIG. DRILLED 20" CONDUCTOR HOLE TO 40' RAN 14" CONDUCTOR PIPE. CMT W/28 SX READY MIX CMT. MIRU BILL MARTIN JR'S RIG #6. DRILLED 12 1/4" SURFACE HOLE TO 1900'. RAN 9 5/8" 32.3# H-40 CSG. CMT W/200 SX @15.8 PPG DROP PLUG DISPLACE W/144 PSI LIFT. PUMP 100 SX TOP JOB PMP 100 SX. PMP 180 SX CMT TO SURFACE. HOLE STAYED FULL. SPUD WELL LOCATION ON 8/27/04 AT 2330 HRS. RECEIVED OCT 0 5 2004 DIV. OF OIL, GAS & MINING REGULATORY ANALYST SHEILA UPCHEGO NAME (PLEASE PRINT)

(This space for State use only)

SIGNATURE

9/21/2004

DATE

STATE OF UTAH

	DEPARTMENT OF NATURAL RESOL	JRCES	
007	5. LEASE DESIGNATION AND SERIAL NUMBER: ML-47062		
SUNDR	Y NOTICES AND REPORT	S ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for proposals to drill drill horizontal	new wells, significantly deepen existing wells below cullaterals. Use APPLICATION FOR PERMIT TO DRILL	urrent bottom-hole depth, reenter plugged wells, or a form for such proposals.	7. UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL OIL WELL	GAS WELL 🗹 OTHER		8. WELL NAME and NUMBER: BONANZA 1023-20
2. NAME OF OPERATOR: WESTPORT OIL & GAS	COMPANY L.P.	-	9. API NUMBER: 4304735662
3. ADDRESS OF OPERATOR: 1368 SOUTH 1200 EAST	TY VERNAL STATE UT ZIF	PHONE NUMBER: (435) 781-7024	10. FIELD AND POOL, OR WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL			
FOOTAGES AT SURFACE: 865'F	SL & 1947'FEL		COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSHIP, RA	NGE, MERIDIAN: SWSE 2 10S 2	23E	STATE: UTAH
11. CHECK APP	ROPRIATE BOXES TO INDICAT	TE NATURE OF NOTICE, REF	PORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
■ NOTICE OF INTENT	ACIDIZE	DEEPEN	REPERFORATE CURRENT FORMATION
(Submit in Duplicate)	ALTER CASING	FRACTURE TREAT	SIDETRACK TO REPAIR WELL
Approximate date work will start:	CASING REPAIR	NEW CONSTRUCTION	TEMPORARILY ABANDON
	CHANGE TO PREVIOUS PLANS	OPERATOR CHANGE	TUBING REPAIR
	CHANGE TUBING	PLUG AND ABANDON	VENT OR FLARE
SUBSEQUENT REPORT (Submit Original Form Only)	CHANGE WELL NAME	PLUG BACK	WATER DISPOSAL
Date of work completion:	CHANGE WELL STATUS	PRODUCTION (START/RESUME)	WATER SHUT-OFF
•	COMMINGLE PRODUCING FORMATIONS	RECLAMATION OF WELL SITE	OTHER: FINAL DRILLING
10/12/2004	CONVERT WELL TYPE	RECOMPLETE - DIFFERENT FORMATIO	ODEDATIONS
12. DESCRIBE PROPOSED OR C	OMPLETED OPERATIONS. Clearly show all p	pertinent details including dates, depths, vol	umes, etc.
FINISHED DRILLING FR	OM 1900' TO 7955'. RAN 4 1/2" REM LITE II @11.0 PPG 3.38 YIE	11.6# I-80 CSG.	
RELEASED CAZA 82 ON	I 10/12/04 AT 2400 HRS.		
			· ·
			OCT 2 5 2004 DIV OF OIL, GAS & MINING

(This space for State use only)

NAME (PLEASE PRIN

SHEILA UPCHEGO

TITLE REGULATORY ANALYST

DATE 10/12/2004

STATE OF UTAH

DEPARTMENT OF NATURAL RESOURCES

DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING	5. LEASE DESIGNATION AND SERIAL NUMBER: ML-47062
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.	7. UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL OIL WELL GAS WELL OTHER	8. WELL NAME and NUMBER: BONANZA 1023-20
2. NAME OF OPERATOR:	9. API NUMBER: 4304735662
WESTPORT OIL & GAS COMPANY L.P.	10. FIELD AND POOL, OR WILDCAT:
3. ADDRESSOF OPERATOR: 1368 S. 1200 E. CITY VERNAL STATE UT ZIP 84078 (435) 781-7024	BONANZA
4. LOCATION OF WELL FOOTAGES AT SURFACE: 865'FSL & 1947'FEL	COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: SWSE 2 10S 23E	STATE: UTAH
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	REPERFORATE CURRENT FORMATION
NOTICE OF INTENT	SIDETRACKTO REPAIR WELL
(Submit in Duplicate) ALTER CASING PRACTORE TRUST	TEMPORARILY ABANDON
Approximate date work will start.	TUBING REPAIR
CHANGE TO FILE MODE AND ADMITCH	VENT OR FLARE
CINICE ISSUE	WATER DISPOSAL
SUBSEQUENT REPORT (Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME)	WATER SHUT-OFF
Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE	OTHER: PRODUCTION
12/6/2004 CONVERT WELL TYPE RECOMPLETE - DIFFERENT FORMATION	START-UP
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volun THE SUBJECT WELL LOCATION WAS PLACED ON PRODUCTION ON 12/6/04 AT 11 PPLEASE REFER TO THE ATTACHED CHRONOLOGICAL WELL HISTORY.	nes, etc.
SHEILA UPCHEGO TITLE REGULATORY	'ANALYST
SIGNATURE DATE 12/7/2004	

(This space for State use only)

RECEIVED DEC 13 2004

WESTPORT OIL & GAS COMPANY, LP CHRONOLOGICAL HISTORY

BONANZA 1023-20

SPUD Air Rig	Surface Casing	Activity		Status
		Build Location, 10%	complete	Caza 82
		Build Location, 35%	complete	Caza 82
		Build Location, 55%	complete	Caza 82
		Build Location, 55%	complete	Caza 82
		Build Location, 75%	complete	Caza 82
		Build Location, 80%	complete	Caza 82
		Build Location, 80%	complete	Caza 82
		Build Location, 90%	complete	Caza 82
		Build Location, 95%	complete	Caza 82
		Build Location, 95%	complete	Caza 82
		Build Location, 95%	complete	Caza 82
		Build Location, 95%	complete	Caza 82
		Build Location, 95%	complete	Caza 82
		Build Location, 95%	complete	Caza 82
		Location Built, WOI	BR	Caza 82
		Location Built, WOI	BR	Caza 82
		Location Built, WOI	BR	Caza 82
		Location Built, WOI	BR	Caza 82
		Location Built, WOI	BR	Caza 82
		WOAR		Caza 82
		WOAR		Caza 82
		WOAR	D=-	Caza 82
			uFCE!	VED
		_	Build Location, 10% Build Location, 35% Build Location, 55% Build Location, 55% Build Location, 55% Build Location, 80% Build Location, 80% Build Location, 90% Build Location, 95% Location Built, WOI WOAR WOAR	Build Location, 10% complete Build Location, 35% complete Build Location, 55% complete Build Location, 55% complete Build Location, 55% complete Build Location, 80% complete Build Location, 80% complete Build Location, 90% complete Build Location, 95% complete Location Built, WOBR MOAR WOAR

DEC 13 2004 DIV. OF OIL, GAS & MINING

9/2/04			WOAR		Caza 82
9/3/04		14" @ 40'	WOAR		Caza 82
9/7/04		14" @ 40'	WOAR		Caza 82
9/8/04		14" @ 40'	WOAR		Caza 82
9/9/04		14" @ 40'	WOAR		Caza 82
9/10/04		14" @ 40'	WOAR		Caza 82
9/13/04		14" @ 40'	WOAR		Caza 82
9/14/04		14" @ 40'	WOAR		Caza 82
9/15/04		14" @ 40'	WOAR		Caza 82
9/16/04		14" @ 40'	WOAR		Caza 82
9/17/04		14" @ 40'	WOAR		Caza 82
9/20/04		14" @ 40'	WOAR		Caza 82
9/21/04		14" @ 40'	WOAR		Caza 82
9/22/04		14" @ 40'	WOAR		Caza 82
9/23/04		14" @ 40'	WOAR		Caza 82
9/24/04		14" @ 40'	WOAR		Caza 82
9/27/04	9/24/04	9 5/8" @ 1875'		WORT	Caza 82
9/28/04	9/24/04	9 5/8" @ 1875'		WORT	Caza 82
9/29/04	9/24/04	9 5/8" @ 1875'		WORT	Caza 82
9/30/04	9/24/04	9 5/8" @ 1875'		WORT	Γ Caza 82
10/1/04	9/24/04	9 5/8" @ 1875'		WORT	Γ Caza 82
10/4/04	TD: 3220' MIRU on 10/2 @ report time	Csg. 9 5/8" @ 1875' /04. Test BOPE, PU BHA	MW: 8.4 , and DP. Drill c	SD: 10/03/04 mt and FE. Drill	DSS: 1 f/ 1900'-3220'. DA
10/5/04	TD: 5250' Drill f/ 3220'5	Csg. 9 5/8" @ 1875' 250'. DA @ report time.	MW: 8.4	SD: 10/03/04	DSS: 2
10/6/04	TD: 6150'	Csg. 9 5/8" @ 1875'	MW: 8.4	SD: 10/03/04	DSS: 3
		5150'. DA @ report time.			
				RECEIV DEC 132	/ED
			,	UEC 132	004
			į	TIV. OF OIL DAG.	

EIV. OF OIL, GAS & MINING

10/7/04

TD: 6860' Csg. 9 5/8" @ 1875' MW: 8.9 SD: 10/03/04 DSS: 4 Drill f/ 6150'-6377'. Close in mud system and start light mud up. Drill to 6860'. DA @ report time.

10/8/04

TD: 7150' Csg. 9 5/8" @ 1875' MW: 9.0 SD: 10/03/04 DSS: 5 Drill f/ 6860'-6865'. TFNB. Repair guide on drum for drill line. TIH and tag bridge @ 5170'. Kelly up and wash through bridge. FIH. Drill to 7150'. DA @ report time.

10/11/04

TD: 7955' Csg. 9 5/8" @ 1875' MW: 8.8 SD: 10/03/04 DSS: 8
Drill f/7150'-7317'. TFNB. Drill to 7925'. Lost returns. Lay down 3 joints and pump LCM pills. Lost 600 bbls mud. Established returns and drill to 7955' TD with partial returns. Short trip 12 stds. CCH and circulate out gas. POOH laying down drill string @ report time.

10/12/04

TD: 7955' Csg. 9 5/8" @ 1875' MW: 8.8 SD: 10/03/04 DSS: 8 Finish POOH laying down drill string. Run and cement 4 ½" Production Casing. Set slip and release rig @ midnight 10/11/04. Rig down rotary tools. Will move to Bonanza 1023-2G this am.

11/24/04

PROG: 7:00 AM (DAY 1) HELD SAFETY MEETING. DRIVING/WORKING IN MUDDY CONDITIONS. RDMO BONANZA#1023-7L. RACK EQUIPMENT. ROAD RIG TO BONANZA#1023-2O. MIRU, SPOT EQUIPMENT W/HELP FROM A CATERPILLAR. NDWH, NUBOP. RU FLOOR & TBG EQUIPMENT. PU & RIH W/3-7/8" BIT & NEW 2-3/8" J-55 TBG. (SLM) TBG WAS DRIFTED. EOT @ 4670' 5:00 PM SWI-SDFN.

NOTE: PRIOR TO MIRU, ON 11/17/04 BIG 4 CEMENTING MIXED & PMPD 50 SX "LEAD" HI FILL W/DIAMOND SEAL, 11.0#, 3.82 YEILD & PMPD 200 SX "TAIL" CLASS G CMT, 15.8#, 1.15 YEILD, 3% CALCIUM CHLORIDE DN 9-5/8" ANNULUS. MP: 200, MR: 2, AP: 200, AR: 2 BPM. ISIP: VACUM. 250 SX TOTAL CMT. (NO SQUEEZE PSI) ALSO SJ RAN A CBL-CCL-GR LOG ON 10/14/04 FROM 1250' TO 7885'. EST CMT TOP @ 1470'. MAX TEMP: 180*

11/29/04

PROG: 7:00 AM (DAY 2) HELD SAFETY MEETING. DRIFTING TBG. EOT @ 4670'. FINISH PU 2-3/8" J-55 TBG & RIH. TAG PBTD @ 7906'. CIRC WL CLEAN W/90 BBLS 2% KCL. POOH. STANDING BACK TBG. LD BIT. NU TO 9-5/8" ANNULUS. PMPD 25 BBLS FRESH WATER @ 100# @ 3 BPM W/RIG PMP. ISIP: 20# CHANGE OUT TOP PIPE RAMS TO BLIND RAMS IN BOP. MIRU DBL JACK TESTERS. PT BOP & 4-1/2" CSG TO 500# & 7500#. (HELD GOOD) RDMO DBL JACK. MIRU CUTTERS. RIH W/PERF GUNS & PERF THE MV @ 7610'-7620' & 7756'-7766' USING 3-3/8" EXP GUNS, 23 GM, O.35, 180* PHASING, 2 SPF, (40 HLS) WHP: 0# RDMO CUTTERS. PREP TO FRAC W/BJ ON MONDAY 11/29/04, 4:30 PM SWI-SDF-HOL-WE.

11/30/04

PROG: FRAC STGS 1, 2, AND 3. RIH SET PLUG & PERF STG 4. PREP TO FRAC STGS 4, 5, AND 6 IN AM.

12/1/04

PROG: 7:00 AM (DAY 4) HELD SAFETY MEETING. W/BJ & CREW. BJ HAD TROUBLE STARTING PMPS & POWER PROBLEMS IN FRAC VAN. (COLD WEATHER) CONTINUE ON W/FRAC.

STAGE #4: SICP: 330#. BRK DN PERFS @ 2489 @ 4 BPM. PMPD 50 BBLS 2% KCL @ 3200 @ 32 BPM. ISIP: 1500, FG: .65. PMPD 1359 BBLS LGHTG 18 GEL & 169,887# 20/40 MESH SD. ISIP: 2000, FG: .72, NPI: 500, MP: 3200, MR: 41, AP: 2850, AR: 40.9 BPM.

DECEIVED

DEC 13 2004

STAGE #5: RIH W/4-1/2" BAKER 5K CBP & PERF GUNS. SET CBP @ 6780'. PERF THE MV @ 6156'-6164' USING 3-3/8" EXP GUNS, 23 GM, 0.35, 90* PHASING, 4 SPF, (32 HLS) WHP: 250, BRK DN PERFS @ 2990' @ 4 BPM. PMPD 34 BBLS 2% KCL @ 3880 @ 33 BPM. ISIP: 1750, FG: .72. PMPD 1108 BBLS LGHTG 17 GEL & 135,796# 20/40 MESH SD, ISIP: 2000, FG: .76, NPI: 250, MP: 3200, MR: 41, AP: 2850, AR: 41 BPM.

STAGE #6: RIH W/4-1/2" BAKER 5K CBP & PERF GUNS. SET CBP @ 6040'. PERF THE WASATCH @ 5330'-5336' & 5485'-5491' USING 3-1/8" HSC GUNS, 12 GM, 0.34, 90* PHASING, 4 SPF, (48 HLS) WHP: 200#. BRK DN PERFS @ 4400 @ 4 BPM. PMPD 38 BBLS 2% KCL @ 4000 @ 33 BPM. ISIP: 1500, FG: .71. PMPD 1706 BBLS LGHTG 17 GEL & 211,820# 20/40 MESH SD. CUT SD EARLY--WANTING TO SCREEN OUT. GOT FLUSHED OK. ISIP: 2350, FG: .87, NPI: 850, MP: 4700, MR: 51, AP: 4360, AR: 50.9 BPM, TOTAL SD: 1,266,785# & TOTAL FLUID: 10,112 BBLS. RIH W/4-1/2" BAKER 5K CBP & SET @ 5230'. POOH. RDMO BJ & CUTTERS. NU DRLG RUBBER. RU TBG EQUIPMENT. PREP TO RIH W/BIT & DRL OUT 6 CBP'S IN AM. 5:30 PM, SWI-SDFN.

12/2/04

PROG: 7:00 AM (DAY 5) HELD SAFETY MEETING. WORKING IN COLD WEATHER. WL HEAD HEATER DIED OVERNIGHT. FOUND WL HEAD FROZE UP. THAW OUT WL HEAD & BOP. PU 3-7/8" BIT, POBS W/R NIPPLE & RIH ON NEW 2-3/8" J-55 TBG TO 5230'. LD 24 JTS ON FLOAT. RU SWVL. ESTABLISH CIRC W/2% KCL W/RIG PMP. (SWVL PROBLEMS)

(DRLG CBP#1) @ 5230'. DRL OUT BAKER 5K CBP IN 30 MIN. 100# DIFF. RIH, TAG SD @ 5912'. CO 128' SD.

(DRLG CBP#2) @ 6040'. DRL OUT BAKER 5K CBP IN 20 MIN. 100# DIFF. RIH, TAG SD @ 6762'. CIRC WL CLEAN. PUH W/EOT ABOVE TOP PERF @ 5200'. DRAIN PMP & LINES. FREEZE PROTECT WL HEAD. 5:30 PM, SWI-SDFN. PREP TO DRL OUT 4 CBP'S IN AM.

12/3/04

PROG: 7:00 AM (DAY 6) HELD SAFETY MEETING. DRLG CBP'S. SICP: 300#. EOT @ 5200'. RIH W/TBG TO 6762'. RU SWVL. ESTB CIRC W/2% KCL W/RIG PMP. CO 22' SD.

(DRLG CBP#3) @ 6780'. DRL OUT BAKER 5K CBP IN 42 MIN. 300# DIFF. RIH, TAG SD @ 7100'. CO 30' SD.

(DRLG CBP#4) @ 7130'. DRL OUT BAKER 5K CBP IN 7 MIN. 0# DIFF. RIH, TAG SD @ 7295'. CO 45' SD.

(DRLG CBP#5) @ 7340'. DRL OUT BAKER 5K CBP IN 7 MIN. 100# DIFF. RIH, TAG SD @ 7480'. CO 30' SD.

(DRLG CBP#6) @ 7510'. DRL OUT BAKER 5K CBP IN 23 MIN. 300# DIFF. RIH, TAG SD @ 7776'. CO 130' SD TO PBTD @ 7906'. CIRC WL CLEAN. RD SWVL. PUH & LAND TBG W/227 JTS NEW 2-3/8" J-55 TBG. EOT @ 7390.68' & R NIPPLE @ 7389.26'. AVG 21/MIN/PLUG & CO 385' SD. NDBOP, NUWH. DROP BALL, PMP OFF THE BIT @ 2300# OPEN WL TO PIT ON 20/64 CHK. FTP: 850#, SICP: 1200#. 3:00 PM TURN WL OVER TO FLW BACK CREW. RD RIG. RACK EQUIP. ORIG LTR: 10,112 BBLS. LTR @ 3:00 PM: 9122 BBLS. ROAD RIG TO BONANZA 1023-2G. SPOT RIG & EQUIP. 5:00 PM, SDFN.

12/6/04

PROG: WELL ON FLOWBACK, FLOWBACK REPORT: CP: 1975#, TP: 1600#, 20/64 CHK, 9 BWPH, 24 HRS, SD: CLEAN, TTL BBLS FLWD: 341, TODAY'S LTR: 7,466 BBLS, LOAD REC TODAY: 341 BBLS, REMAINING LTR: 7,125 BBLS, TOTAL LOAD REC TO DATE: 2,987 BBLS.

RECEIVED DEC 13 2004

TIV. OF OIL, GAS & MINING

FIECEIVED

CEC 1 3 2004

TY GEO'L, GAS & MINING

FORM 8 AMENDED REPORT STATE OF UTAH (highlight changes) DEPARTMENT OF NATURAL RESOURCES 5. LEASE DESIGNATION AND SERIAL NUMBER: DIVISION OF OIL, GAS AND MINING ML-47062 6. IF INDIAN, ALLOTTEE OR TRIBE NAME WELL COMPLETION OR RECOMPLETION REPORT AND LOG 7. UNIT or CA AGREEMENT NAME 1a. TYPE OF WELL: GAS VIEL OIL 8. WELL NAME and NUMBER: b. TYPE OF WORK: **BONANZA 1023-20** DIFF. RESVR. RE-ENTRY OTHER WEYL 🔽 9. API NUMBER: 2. NAME OF OPERATOR: 4304735662 WESTPORT OIL & GAS COMPANY L.P. 10 FIELD AND POOL, OR WILDCAT PHONE NUMBER: 3. ADDRESS OF OPERATOR: (435) 781-7024 BONANZA STATE UT ZIP 84078 CITY VERNAL 1368 S. 1200 E. 11. QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: 4. LOCATION OF WELL (FOOTAGES) AT SURFACE: 865'FSL & 1947'FEL SWSE 2 10S 23E AT TOP PRODUCING INTERVAL REPORTED BELOW: 13. STATE 12. COUNTY UTAH UINTAH AT TOTAL DEPTH: 17. ELEVATIONS (DF, RKB, RT, GL): 16. DATE COMPLETED: 15. DATE T.D. REACHED: 14. DATE SPUDDED: READY TO PRODUCE 🔽 ABANDONED 🔲 5457'GL 12/6/2004 10/11/2004 8/27/2004 21. DEPTH BRIDGE 20. IF MULTIPLE COMPLETIONS, HOW MANY? * 19. PLUG BACK T.D.: MD 7.906 18. TOTAL DEPTH: MD 7.955 TVD 22. TYPE ELECTRIC AND OTHER MECHANICAL LOGS RUN (Submit copy of each) NO 🔽 YES (Submit analysis) VCBL-CCL-GRI RESEVOIR SAT LOG WAS WELL CORED? NO 🗸 YES (Submit report) WAS DST RUN? ио 🇸 (Submit copy) YES DIRECTIONAL SURVEY? 24. CASING AND LINER RECORD (Report all strings set in well) CEMENT TYPE & NO. OF SACKS STAGE CEMENTER SLUBBY CEMENT TOP ** AMOUNT PULLED BOTTOM (MD) VOLUME (BBL) TOP (MD) WFIGHT (#/ft.) HOLE SIZE SIZE/GRADE DEPTH 28 40 54# 20" 580 1.900 32.3# 9 5/8 H-40 12 1/4 1800 7.955 11.6# 4 1/2 I-80 7 7/8 25. TUBING RECORD PACKER SET (MD) DEPTH SET (MD) SIZE PACKER SET (MD) DEPTH SET (MD) SIZE PACKER SET (MD) DEPTH SET (MD) 7.391 2 3/8 27. PERFORATION RECORD 26. PRODUCING INTERVALS PERFORATION STATUS NO. HOLES INTERVAL (Top/Bot - MD) SIZE BOTTOM (TVD) TOP (TVD) TOP (MD) BOTTOM (MD) FORMATION NAME Open 🔽 Squeezed 0.34 48 5.330 5,491 5.491 5,330 (A) WASATCH Squeezed 200 7.766 0.35 Open 6,154 7.766 (B) MESAVERDE 6.154 Squeezed Open (C) (D) 28. ACID, FRACTURE, TREATMENT, CEMENT SQUEEZE, ETC. AMOUNT AND TYPE OF MATERIAL DEPTH INTERVAL PMP 1706 BBLS LIGHTNING 17 GEL & 211,820# 20/40 MESH SD 5330'-5491' PMP 8406 BBLS LIGHTNING 18 GEL & 1,054,965# 20/40 MESH SD 6154'-7766' 30. WELL STATUS: 29. ENCLOSED ATTACHMENTS: DST REPORT DIRECTIONAL SURVEY GEOLOGIC REPORT PRODUCING ELECTRICAL/MECHANICAL LOGS OTHER: CORE ANALYSIS SUNDRY NOTICE FOR PLUGGING AND CEMENT VERIFICATION 3 (CONTINUED ON BACK) (5/2000)b

DIV OF OIL, GAS & MINING

731. IŅITIAL PRO	DUCTION				IN	TERVAL A (As show					Lange METUCS
DATE FIRST PRO		TEST DAT	TE:		HOURS TEST		TEST PRODUCTION		GAS - MCF:	WATER BB 360	L; PROD. METHOD: FLOWING
12/6/2004		12/15	/2004			24	RATES: →	0	2,170		
CHOKE SIZE: 64/64	TBG. PRESS. 1,055	CSG. PRE		GRAVITY	BTU – GAS	GAS/OIL RATIO	24 HR PRODUCTION RATES: →	OIL – BBL:	GAS - MCF: 2,170	WATER - BB 360	L: INTERVAL STATUS: PRODUCING
04/04	1,000	1,00	,,,		<u> </u>	ITERVAL B (As sho	wn in item #26)	l			
DATE FIRST PRO	DDUCED:	TEST DAT	TE:		HOURS TEST		TEST PRODUCTION	OIL ~ BBL:	GAS - MCF:	WATER - BB	
12/6/2004			/2004			24	RATES: →	0	2,170	360	FLOWING
CHOKE SIZE:	TBG. PRESS.	CSG. PRE	ESS. API	GRAVITY	BTU – GAS	GAS/OIL RATIO	24 HR PRODUCTION		GAS MCF:	WATER - BB	IL: INTERVAL STATUS:
64/64	1,055	1,33	30				RATES: →	0	2,170	360	PRODUCING
					11	ITERVAL C (As sho	wn in item #26)				
DATE FIRST PRO	ODUCED:	TEST DA	TE:		HOURS TEST	ED:	TEST PRODUCTION RATES: →	OIL – BBL:	GAS MCF:	WATER - BE	
CHOKE SIZE:	TBG. PRESS.	CSG. PRI	ESS. API	GRAVITY	BTU - GAS	GAS/OIL RATIO	24 HR PRODUCTION RATES: →	OIL - BBL:	GAS MCF:	WATER - BB	IL: INTERVAL STATUS:
					11	ITERVAL D (As sho	wn in item #26)				
DATE FIRST PRO	ODUCED:	TEST DATE:		<u> </u>	HOURS TESTED:		TEST PRODUCTION RATES: →	OIL - BBL:	GAS - MCF:	WATER - BE	BL: PROD. METHOD:
CHOKE SIZE:	TBG. PRESS.	CSG. PRI	ESS. API	I GRAVITY	BTU - GAS GAS/OIL RATIO		24 HR PRODUCTION RATES: →	N OIL – BBL:	GAS MCF:	WATER - BE	BL: INTERVAL STATUS
32. DISPOSITIO	N OF GAS (Sol	d, Used for F	uel, Vented	i, Etc.)							
33. SUMMARY	OE POPOLIS 70	NES (include	e Agulfers):				:	34. FORMATION	(Log) MARKERS:		
	at zonge of naro	eity and conte	ants thereof	Cored interva	als and all drill-st recoveries.	em tests, including d	epth interval				
Formation	on	Top (MD)	Bottom (MD)		Desc	riptions, Contents, et	c.		Name		Top (Measured Depth)
WASATCH MESAVER		4,027 6,133	6,133	3							
	į										

35. ADDITIONAL REMARKS (include plugging procedure)

NOTE: PRIOR TO MIRU, ON 11/17/04BIG 4 CEMENTING MIXED & PMPD 50 SX "LEAD" HI FILL W/DIAMOND SEAL, 11.0#, 3.82 YEILD & PMPD 200 SX "TAIL" CLASS G CMT, 15.8#, 1.15 YEILD, 3% CALCIUM CHLORIDE DN 9-5/8". ANNULUS. MP: 200, MR: 2, AP: 200, AR: 2 BPM. ISIP: VACUM. 250 SX TOTAL CMT. (NO SQUEEZE PSI) ALSO SJ RAN A CBL-CCL-GR LOG ON 10/14/04 FROM 1250' TO 7885'. EST CMT TOP @ 1470'. MAX TEMP: 180*

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

TITLE REGULATORY ANALYST

DATE 12/28/2004

This report must be submitted within 30 days of

• completing or plugging a new well

drilling horizontal laterals from an existing well bore

recompleting to a different producing formation

- reentering a previously plugged and abandoned well
- significantly deepening an existing well bore below the previous bottom-hole depth
- drilling hydrocarbon exploratory holes, such as core samples and stratigraphic tests

* ITEM 20: Show the number of completions if production is measured separately from two or more formations.

** ITEM 24: Cement Top – Show how reported top(s) of cement were determined (circulated (CIR), calculated (CAL), cement bond log (CBL), temperature survey (TS)).

Send to:

Utah Division of Oil, Gas and Mining 1594 West North Temple, Suite 1210

Box 145801

Salt Lake City, Utah 84114-5801

Phone: 801-538-5340

Fax: 801-359-3940

Division of Oil, Gas and Mining OPERATOR CHANGE WORKSHEET

	ROUTING
i	1. DJJ
	2. CDW

X Change of Operator (Well Sold)

Operator Name Change/Merger

The operator of the well(s) listed below has changed, effective:	-11		1/6/2006					
FROM: (Old Operator):	TO: (New Op	erator):						
N2115-Westport Oil & Gas Co., LP	N2995-Kerr-M	-	as Onshor	e, LP				
1368 South 1200 East	1368 S	outh 1200	East					
Vernal, UT 84078	Vernal, UT 84078							
Phone: 1-(435) 781-7024	Phone: 1-(435)	781-7024						
CA No.	Unit:							
WELL NAME SEC TWN RNG		ENTITY NO	LEASE TYPE	WELL TYPE	WELL STATUS			
OPERATOR CHANGES DOCUMENTATION								
Enter date after each listed item is completed								
1. (R649-8-10) Sundry or legal documentation was received from the	FORMER ope	rator on:	5/10/2006					
2. (R649-8-10) Sundry or legal documentation was received from the	NEW operator	on:	5/10/2006	•				
3. The new company was checked on the Department of Commerce .	-		s Database o	on:	3/7/2006			
	Business Numb	_	1355743-018					
4b. If NO, the operator was contacted contacted on:				•				
5a. (R649-9-2)Waste Management Plan has been received on:	IN PLACE							
5b. Inspections of LA PA state/fee well sites complete on:	n/a	•						
5c. Reports current for Production/Disposition & Sundries on:	ok	•						
6. Federal and Indian Lease Wells: The BLM and or the B	IA has appro	ved the r	nerger, nan	ne chan	ge,			
or operator change for all wells listed on Federal or Indian leases of		BLM	3/27/2006		not yet			
7. Federal and Indian Units:								
The BLM or BIA has approved the successor of unit operator for	wells listed on:		3/27/2006					
8. Federal and Indian Communization Agreements ("C	•							
The BLM or BIA has approved the operator for all wells listed w			n/a					
·· 8	vision has appro			sfer of A	uthority to			
Inject, for the enhanced/secondary recovery unit/project for the wa	ter disposal wel	l(s) listed	on;					
DATA ENTRY:								
1. Changes entered in the Oil and Gas Database on:	5/15/2006		E/1 E/200C					
 Changes have been entered on the Monthly Operator Change Sp. Bond information entered in RBDMS on: 			5/15/2006	-				
3. Bond information entered in RBDMS on:4. Fee/State wells attached to bond in RBDMS on:	5/15/2006 5/16/2006	-						
5. Injection Projects to new operator in RBDMS on:	3/10/2000	•						
6. Receipt of Acceptance of Drilling Procedures for APD/New on:		n/a	Name Chan	oe Only				
BOND VERIFICATION:		10 4	Traine Chan	ge omy				
Federal well(s) covered by Bond Number:	CO1203							
2. Indian well(s) covered by Bond Number:	RLB0005239	•						
3. (R649-3-1) The NEW operator of any fee well(s) listed covered by		-	RLB000523	6				
a. The FORMER operator has requested a release of liability from the		n/a	rider adde					
The Division sent response by letter on:			_					
LEASE INTEREST OWNER NOTIFICATION:		_'						
4. (R649-2-10) The FORMER operator of the fee wells has been containing	acted and inform	ned by a le	tter from the	Division				
of their responsibility to notify all interest owners of this change on		5/16/2006	5					
COMMENTS:								

4 Form 3 160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0135 Expires Jnovember 30, 2000

BUREAU OF LAND MANAGEMENT 5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

MULTIPLE LEASES

Do not use this abandoned well.	6. If Indian, A	lottee or Tribe 1	Varne			
SUBMIT IN TRIPL	ICATE – Other instru	7. If Unit or C.	A/Agreement, N	ame and/or No.		
1. Type of Well Oil Well Gas Well	Other			8. Well Name	and No.	
2. Name of Operator				MUTIPLE	WELLS	
KERR-McGEE OIL & GAS (DNSHORE LP			9. API Well No		
3a. Address		3b. Phone No. (inch	ude area code)	1		
1368 SOUTH 1200 EAST V	'ERNAL, UT 84078	(435) 781-7024		10. Field and Po	ol, or Explorato	ry Area
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Descript	ion)		1		
				11. County or P	arish, State	
SEE ATTACHED				UINTAH CO	UNTY, UTA	\H
12. CHECK APP	ROPRIATE BOX(ES) TO	INDICATE NATURE	OF NOTICE, F	REPORT, OR OT	THER DATA	***
TYPE OF SUBMISSION			PE OF ACTION			
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production	ı (Start/Resume)	Water Shut Well Integr	
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandor	Recomplet			ANGE OF
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disp	=	0, 2,0,10	
13. Describe Proposed or Completed Open If the proposal is to deepen directional Attach the Bond under which the work following completion of the involved testing has been completed. Final All determined that the site is ready for final	illy or recomplete horizontally, go rk will be performed or provide operations. If the operation resident bandonment Notices shall be fil	give subsurface locations a the Bond No. on file with ults in a multiple completi	nd measured and tru h BLM/BIA. Requi on or recompletion	te vertical depths of ired subsequent repo in a new interval a	all pertinent mar orts shall be filed Form 3160-4 sha	kers and zones. within 30 days all he filed once
PLEASE BE ADVISED THAT OPERATOR OF THE ATTAK KERR-McGEE OIL & GAS CO OF THE LEASE(S) FOR THE IS PROVIDED BY STATE OF BLATE BLA	CHED WELL LOCATIONSHORE LP, IS RESE OPERATIONS CONFUTANTIONWIDE ON SECOND SECON	ONS. EFFECTIVE SPONSIBLE UNDE IDUCTED UPON I E BOND NO. RLB A 005239	E JANUARY 6 ER TERMS AN LEASE LAND 0005237. PPROVE	S, 2006. ND CONDITIONS. BOND CO	DNS VERAGE 5/06 ^{DIV.}	RECEIVED MAY 1 0 2006 OF OIL, GAS & MINING
Name (Printed/Typed)	g is true and confect			Engineering		

DRILLING MANAGER Date May 9, 2006 THIS SPACE FOR FEDERAL OR STATE USE Approved by Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office Title 18 U.S.C. Section 1001, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Form 3 160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0135 Expires Inovember 30, 2000

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

MULTIPLE LEASES

Do not use this abandoned well.	6. If Indian, Allottee or Tribe Name							
SUBMIT IN TRIPL	SUBMIT IN TRIPLICATE – Other instructions on reverse side							
1. Type of Well								
Oil Well X Gas Well	Other		8. Well Name and No.					
2. Name of Operator			MUTIPLE WELLS					
WESTPORT OIL & GAS CO	MPANY L.P.		9. API Well No.					
3a. Address	3b.	Phone No. (include are	ea code)					
1368 SOUTH 1200 EAST V	ERNAL, UT 84078 (435) 781-7024	10. Field and Pool, or Exploratory Area					
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Description)							
			11. County or Parish, State					
SEE ATTACHED			UINTAH COUNTY, UTAH					
	ROPRIATE BOX(ES) TO INDIC	ATE NATURE OF N	NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION		ТҮРЕ О	DF ACTION					
Notice of Intent Subsequent Report	Alter Casing F	Peepen	Production (Start/Resume) Water Shut-Off Reclamation Well Integrity Recomplete X Other CHANGE OF					
		lug and Abandon 📋	Temporarily Abandon OPERATOR					
Final Abandonment Notice	Convert to Injection P	lug Back	Water Disposal					
testing has been completed. Final Aldetermined that the site is ready for fin EFFECTIVE JANUARY 6, 20 THE OPERATORSHIP OF 1	bandonment Notices shall be filed only a lal inspection. 006, WESTPORT OIL & GA	after all requirements, in	·					
ONSHORE LP.	APPROV	/ED <u>5/6</u>	106					
	Λ .							
	Carlo	ne Russel	MAY 1 0 2006					
	Division of O	il, Gas and Minin	ng 1974 U 2006					
	Dariene Kusse	oli, Engineering T	DIV. OF OIL GAS & MINING					
14. I hereby certify that the foregoin	_							
Name (Printed/Typed)		itle	SECIALIST					
BRAD LANEY Signature		NGINEERING SP	PECIALIST					
o i griaturo	_	ay 9, 2006						
	THIS SPACE FOR	FEDERAL OR STAT	TE USE					
Approved by		Title	Date					
Grad Janus			5-9-06					
Conditions of approval, if any, are attached certify that the applicant holds legal of equ								
which would entitle the applicant to conduc	t operations thereon.							
Title 18 U.S.C. Section 1001, make	it a crime for any person knowingly	and willfully to make	e to any department or agency of the United States any					

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

SIAILOLOIAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

***************************************			ENTITY ACTION	FORM		· · · · · · · · · · · · · · · · · · ·			
)norotor:	KERR	McGEE OIL & GAS ON	JSHORE LP					2005	
perator:		ox 173779	umber: _l	<u>// таар</u>					
ddress:	-		······································	-					
	city DE			-					
	state C	O	_{zip} 80217	_	P	hone Nu	ımber: _	(720) 929-6029	
Weil 1									
API N	umber	Well	Name	QQ	Sec	Twp	Rng	County	
See A	Atchmt	See Atchn	nt			,			
Action	Code	Current Entity Number	New Entity Number	S	Spud Da	te		tity Assignment Effective Date	
		99999	19519				<u></u>		
Commen	its:						1 0/	115019	
WSM		e see attachment with	list of Wells in the Pon	derosa Uı 	nit.		513	30 12012	
Veil 2									
API No	umber	Well	Name	Sec	Twp	Rng	County		
						,			
Action	Code	Current Entity Number	New Entity Number	s	pud Dat	te	Entity Assignment Effective Date		
·									
Commen	its:								
						· · · · · · · · · · · · · · · · · · ·			
Nell 3 API Nu	ımber	Wall	Name	T 00	Г	I			
71111	arriber .	VVEIL	name	QQ	Sec	Twp	Rng	County	
Action	Code	Current Entity Number	New Entity Number	s	pud Dat	 :e		ity Assignment	
Commen	ts:	-					·		
ION COD		maliku dina manung ti da b		Cov	ra Mahle	_			
A - EstaB - Add	new well to	ntity for new well (single existing entity (group or	well only) unit well)						
C - Re-a	assign well f	rom one existing entity to	another existing entity	Nam	e (Please	LLIUI)			
D - Re-a	assign well f	rom one existing entity to	a new entity		ature				
E - Othe	er (Explain i	n 'comments' section)	RECEIVED	REG	GULATO	RY ANA	LYST	5/21/2012	
			MAV a 4 2042	Title				Date	

(5/2000)

MAY 2 1 2012

well name	sec	twp	rng	api	entity	le	ease	well	stat	qtr_qtr	bhl	surf zone	a_stat	I_num	op_no
SOUTHMAN CANYON 31-3	31	090S	230E	4304734726	13717		1	GW	Р	SENW		1 WSMVD	P	U-33433	N2995
SOUTHMAN CANYON 31-4	31	090S	230E	4304734727	13742			GW	S	SESW		1 WSMVD	S	UTU-33433	N2995
SOUTHMAN CYN 31-2X (RIG SKID)	31	0908	230E	4304734898	13755		1	GW	Р	NWNW		1 WSMVD	Р	U-33433	N2995
SOUTHMAN CYN 923-31J	31	090S	230E	4304735149				GW	Р	NWSE		1 MVRD	Р	U-33433	N2995
SOUTHMAN CYN 923-31B	31	0908	230E	4304735150				GW	Р	NWNE		1 MVRD	Р	U-33433	N2995
SOUTHMAN CYN 923-31P	31	0908	230E	4304735288	14037			GW	Р	SESE		1 WSMVD	Р	UTU-33433	N2995
SOUTHMAN CYN 923-31H	31	090S	230E	4304735336	14157			GW	Р	SENE		1 WSMVD	Р	U-33433	N2995
SOUTHMAN CYN 923-310	31	090S	230E	4304737205			1	GW	Р	SWSE		1 MVRD	Р	UTU-33433	N2995
SOUTHMAN CYN 923-31K	31	090S	230E	4304737206	16503		1	GW	Р	NESW		1 WSMVD	Р	UTU-33433	N2995
SOUTHMAN CYN 923-31G	31	090S	230E	4304737208	16313		1	GW	Р	SWNE		1 WSMVD	Р	UTU-33433	N2995
SOUTHMAN CYN 923-31E	31	0908	230E	4304737209	16521		1	GW	Р	SWNW		1 WSMVD	Р	UTU-33433	N2995
SOUTHMAN CYN 923-31A	31	090S	230E	4304737210	16472		1	GW	Р	NENE		1 WSMVD	Р	UTU-33433	N2995
SOUTHMAN CYN 923-31C	31	090S	230E	4304737227	16522		1	GW	Р	NENW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-1G	01	100S	230E	4304735512	14458		1	GW	Р	SWNE		1 WSMVD	Р	U-40736	N2995
BONANZA 1023-1A	01	100S	230E	4304735717	14526		1	GW	Р	NENE		1 WSMVD	Р	U-40736	N2995
BONANZA 1023-1E	01	100S	230E	4304735745	14524		1	GW	Р	SWNW		1 WSMVD	Р	U-40736	N2995
BONANZA 1023-1C	01	100S	230E	4304735754	14684		1	GW	Р	NENW		1 MVRD	Р	U-40736	N2995
BONANZA 1023-1K	01	100S	230E	4304735755	15403		1	GW	Р	NESW		1 MVRD	Р	U-38423	N2995
BONANZA 1023-1F	01	100S	230E	4304737379	16872		1	GW	Р	SENW		1 MVRD	Р	UTU-40736	N2995
BONANZA 1023-1B	01	100S	230E	4304737380	16733		1	GW	Р	NWNE		1 MVRD	Р	UTU-40736	N2995
BONANZA 1023-1D	01	100S	230E	4304737381	16873		1	GW	Р	NWNW		1 MVRD	Р	UTU-40736	N2995
BONANZA 1023-1H	01	100S	230E	4304737430	16901		1	GW	Р	SENE		1 MVRD	Р	UTU-40736	N2995
BONANZA 1023-1L	01	100S	230E	4304738300	16735		1	GW	Р	NWSW		1 MVRD	Р	UTU-38423	N2995
BONANZA 1023-1J	01	100S	230E	4304738302	16871		1	GW	Р	NWSE		1 MVRD	Р	UTU-40736	N2995
BONANZA 1023-1I	01	100S	230E	4304738810	16750		1	GW	Р	NESE		1 MVRD	Р	UTU-40736	N2995
BONANZA 1023-2E	02	100S	230E	4304735345	14085		3	GW	Р	SWNW		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2C	02	100S	230E	4304735346	14084		3	GW	Р	NENW		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2A	02	100S	230E	4304735347	14068		3	GW	Р	NENE		3 MVRD	Р	ML-47062	N2995
BONANZA 1023-2G	02	100S	230E	4304735661	14291		3 (GW	Р	SWNE		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-20	02	100S	230E	4304735662	14289		3 (GW	Р	SWSE		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2I	02	100S	230E	4304735663	14290		3 (GW	S	NESE		3 WSMVD	S	ML-47062	N2995
BONANZA 1023-2MX	02	100S	230E	4304736092	14730		3 (GW	Р	swsw		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2H	02	100S	230E	4304737093	16004		3 (GW	Р	SENE		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2D	02	100S	230E	4304737094	15460		3 (GW	Р	NWNW		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2B	02	100S	230E	4304737095	15783		3 (GW	Р	NWNE		3 MVRD	Р	ML-47062	N2995
BONANZA 1023-2P	02	100S	230E	4304737223	15970		3 (GW	Р	SESE		3 WSMVD	Р	ML-47062	N2995
BONANZA 1023-2N	02	100S	230E	4304737224	15887		3 (GW	Р	SESW		3 MVRD	Р	ML-47062	N2995
BONANZA 1023-2L	02		230E	4304737225	15833			ЭW	Р	NWSW		3 WSMVD		ML-47062	N2995
BONANZA 1023-2F	02		230E	4304737226	15386				Р	SENW		3 WSMVD	+	ML-47062	N2995
BONANZA 1023-2D-4	02		230E	4304738761	16033				Р	NWNW	-	3 WSMVD		ML-47062	N2995
BONANZA 1023-20-1	02	100S	230E	4304738762	16013				Р	SWSE		3 WSMVD	+	ML-47062	N2995
BONANZA 1023-2H3CS	02		230E	4304750344	17426				Р	1	D	3 MVRD		ML 47062	N2995
BONANZA 1023-2G3BS	02	100S	230E	4304750345	17428				Р		D	3 MVRD	·i	ML 47062	N2995
BONANZA 1023-2G2CS	02		230E	4304750346	17429				Р		D	3 MVRD		ML 47062	N2995
BONANZA 1023-2G1BS	02		230E	4304750347	17427				Р	 	D	3 MVRD		ML 47062	N2995

								_					
BONANZA 1023-2M1S	02	100S	230E	4304750379	17443	3 GW	Р	SENW	D	3 MVRD	P	ML 47062	N2995
BONANZA 1023-2L2S	02	100S	230E	4304750380	17444	3 GW	Р	SENW	D	3 MVRD	Р	ML 47062	N2995
BONANZA 1023-2K4S	02	100S	230E	4304750381	17446	3 GW	Р	SENW	D	3 MVRD	Р	ML 47062	N2995
BONANZA 1023-2K1S	02	100S	230E	4304750382	17445	3 GW	Р	SENW	D	3 WSMVD	Р	ML 47062	N2995
BONANZA 4-6 🚁	04	100S	230E	4304734751	13841	1 GW	Р	NESW	İ	1 MNCS	Р	UTU-33433	N2995
BONANZA 1023-4A	04	100S	230E	4304735360	14261	1 GW	Р	NENE		1 WSMVD	Р	U-33433	N2995
BONANZA 1023-4E	04	100S	230E	4304735392	14155	1 GW	P	SWNW		1 WSMVD	Р	U-33433	N2995
BONANZA 1023-4C	04	100S	230E	4304735437	14252	1 GW	Р	NENW		1 WSMVD	Р	U-33433	N2995
BONANZA 1023-4M	04	100S	230E	4304735629	14930	1 GW	Р	SWSW		1 WSMVD	Р	U-33433	N2995
BONANZA 1023-40	04	100S	230E	4304735688	15111	1 GW	P	SWSE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-4I	04	100S	230E	4304735689	14446	1 GW	Р	NESE		1 MVRD	Р	UTU-33433	N2995
BONANZA 1023-4G	04	100S	230E	4304735746	14445	1 GW	Р	SWNE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-4D	04	100S	230E	4304737315	16352	1 GW	Р	NWNW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-4H	04	100S	230E	4304737317	16318	1 GW	Р	SENE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-4B	04	100S	230E	4304737328	16351	1 GW	Р	NWNE		1 MVRD	Р	UTU-33433	N2995
BONANZA 1023-4L	04	100S	230E	4304738211	16393	1 GW	Р	NWSW		1 MVRD	Р	UTU-33433	N2995
BONANZA 1023-4P	04	100S	230E	4304738212	16442	1 GW	Р	SESE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-4N	04	100S	230E	4304738303	16395	1 GW	Р	SESW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-4FX (RIGSKID)	04	100S	230E	4304739918	16356	1 GW	Р	SENW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-50	05	100S	230E	4304735438	14297	1 GW	Р	SWSE		1 WSMVD	Р	U-33433	N2995
BONANZA 1023-5AX (RIGSKID)	05	100S	230E	4304735809	14243	1 GW	Р	NENE		1 WSMVD	Р	U-33433	N2995
BONANZA 1023-5C	05	100S	230E	4304736176	14729	1 GW	Р	NENW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5G	05	100S	230E	4304736177	14700	1 GW	Р	SWNE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5M	05	100S	230E	4304736178	14699	1 GW	Р	SWSW		1 WSMVD	Р	UTU-73450	N2995
BONANZA 1023-5K	05	100S	230E	4304736741	15922	1 GW	Р	NESW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5B	05	100S	230E	4304737318	16904	1 GW	Р	NWNE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5E	05	100S	230E	4304737319	16824	1 GW	Р	SWNW		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5H	05	100S	230E	4304737320	16793	1 GW	Р	SENE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5N	05	100S	230E	4304737321	16732	1 GW	Р	SESW	-	1 WSMVD	Р	UTU-73450	N2995
BONANZA 1023-5L	05	100S	230E	4304737322	16825	1 GW	Р	NWSW		1 MVRD	Р	UTU-33433	N2995
BONANZA 1023-5J	05	100S	230E	4304737428	17055	1 GW	Р	NWSE		1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5P	05	100S	230E	4304738213	16795	1 GW	Р	SESE		1 MVRD	Р	UTU-33433	N2995
BONANZA 1023-5N-1	05	100S	230E	4304738911	17060	1 GW	Р	SESW		1 WSMVD	Р	UTU-73450	N2995
BONANZA 1023-5PS	05	100S	230E	4304750169	17323	1 GW	Р	NESE	D	1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-5G2AS	05	100S	230E	4304750486	17459	1 GW	Р	SWNE	D	1 MVRD	Р	UTU 33433	N2995
BONANZA 1023-5G2CS	05	100S	230E	4304750487	17462	1 GW	Р	SWNE	D	1 MVRD	Р	UTU 33433	N2995
BONANZA 1023-5G3BS	05	100S	230E	4304750488	17461	1 GW	Р	SWNE	D	1 MVRD	P	UTU 33433	N2995
BONANZA 1023-5G3CS	05	100S	230E	4304750489	17460	1 GW	Р	SWNE	D	1 MVRD	Р	UTU 33433	N2995
BONANZA 1023-5N4AS	05	100S	230E	4304752080	18484	1 GW	DRL	swsw	D	1 WSMVD	DRL	UTU73450	N2995
BONANZA 1023-8C2DS	05	100S	230E	4304752081	18507	1 GW	DRL	swsw	D	1 WSMVD	DRL	UTU37355	N2995
BONANZA 6-2	06	100S	230E	4304734843	13796	1 GW	TA	NESW		1 WSMVD	TA	UTU-38419	N2995
BONANZA 1023-6C	06	100S	230E	4304735153	13951	1 GW	Р	NENW		1 MVRD	Р	U-38419	N2995
BONANZA 1023-6E	06	1008	230E	4304735358	14170	1 GW	Р	SWNW		1 MVRD	Р	U-38419	N2995
BONANZA 1023-6M	06	100S	230E	4304735359	14233	1 GW	Р	SWSW		1 WSMVD	Р	U-38419	N2995
BONANZA 1023-6G	06	100S	230E	4304735439	14221	1 GW	Р	SWNE		1 WSMVD	Р	UTU-38419	N2995
BONANZA 1023-60	06	100S	230E	4304735630	14425	1 GW	TA	SWSE		1 WSMVD	TA	U-38419	N2995

* \$ · _ , ·

DOMANZA 1022 CA	06	1000	220⊏	4204726067	14775	4	C\\\	Р	NENE	1	1 WSMVD	Р	11 22422	N2995
BONANZA 1023-6A	06	1008	230E	4304736067	14775		GW	P	NENE SESW		1 WSMVD	P	U-33433 UTU-38419	N2995 N2995
BONANZA 1023-6N	06	1008	230E	4304737211 4304737212	15672 15673	- 	GW	P	NWSW		1 WSMVD	P	UTU-38419	N2995 N2995
BONANZA 1023-6L	06	1008	230E		15620		GW	P	NWSE	1	1 WSMVD	P	UTU-38419	N2995 N2995
BONANZA 1023-6J	06	1008	230E	4304737213			<u> </u>			-				
BONANZA 1023-6F	06	1008	230E	4304737214	15576		GW	TA	SENW	1	1 WSMVD	TA	UTU-38419	N2995
BONANZA 1023-6P	06	1008	230E	4304737323	16794		GW	P	SESE	-	1 WSMVD	Р	UTU-38419	N2995
BONANZA 1023-6H	06	100\$	230E	4304737324	16798		GW	S	SENE	-	1 WSMVD	S	UTU-33433	N2995
BONANZA 1023-6D	06	1008	230E	4304737429	17020		GW	P	NWNW	-	1 WSMVD	P	UTU-38419	N2995
BONANZA 1023-6B	06	100S	230E	4304740398	18291		GW	P	NWNE	ļ	1 WSMVD	Р	UTU-33433	N2995
BONANZA 1023-6M1BS	06	100S	230E	4304750452	17578		GW	P	NWSW	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-6N1AS	06	100\$	230E	4304750453	17581	ii	GW	Р	NWSW	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-6N1CS	06	100S	230E	4304750454	17580		GW	Р	NWSW	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-6N4BS	06	100S	230E	4304750455	17579		GW	Р	NWSW	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-612S	06	100S	230E	4304750457	17790		GW	Р	NESE	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-614S	06	100S	230E	4304750458	17792		GW	Р	NESE	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-6J3S	06	100S	230E	4304750459	17791	1	GW	Р	NESE	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-6P1S	06	100S	230E	4304750460	17793	1	GW	Р	NESE	D	1 WSMVD	Р	UTU 38419	N2995
BONANZA 1023-6A2CS	06	100S	230E	4304751430	18292	1	GW	Р	NWNE	D ·	1 WSMVD	Р	UTU33433	N2995
BONANZA 1023-6B4BS	06	100S	230E	4304751431	18293	1	GW	Р	NWNE	D	1 WSMVD	Р	UTU33433	N2995
BONANZA 1023-6B4CS	06	100S	230E	4304751432	18294	1	GW	Р	NWNE	D	1 WSMVD	Р	UTU33433	N2995
BONANZA 1023-6C4BS	06	100S	230E	4304751449	18318	1	GW	Р	NENW	D	1 WSMVD	Р	UTU38419	N2995
BONANZA 1023-6D1DS	06	1008	230E	4304751451	18316		GW	Р	NENW	D	1 WSMVD	Р	UTU38419	N2995
FLAT MESA FEDERAL 2-7	07	1008	230E	4304730545	18244		GW	S	NENW		1 WSMVD	S	U-38420	N2995
BONANZA 1023-7B	07	100S	230E	4304735172	13943		GW	Р	NWNE		1 MVRD	Р	U-38420	N2995
BONANZA 1023-7L	07	100S	230E	4304735289	14054		GW	Р	NWSW		1 WSMVD	Р	U-38420	N2995
BONANZA 1023-7D	07	100S	230E	4304735393	14171		GW	Р	NWNW		1 WSMVD	P	U-38420	N2995
BONANZA 1023-7P	07	100S	230E	4304735510	14296		GW	Р	SESE		1 WSMVD	Р	U-38420	N2995
BONANZA 1023-7H	07	100S	230E	4304736742	15921		GW	P	SENE	1	1 WSMVD	P	UTU-38420	N2995
BONANZA 1023-7NX (RIGSKID)	07	100S	230E	4304736932	15923		GW	P	SESW		1 WSMVD	P		N2995
BONANZA 1023-7M	07	100S	230E	4304737215	16715		GW	P	SWSW		1 WSMVD	P		N2995
BONANZA 1023-7K	07	1005	230E	4304737216	16714		GW	P	NESW		1 WSMVD	P	UTU-38420	N2995
BONANZA 1023-7E	07	1005	230E	4304737217	16870		GW	P	SWNW		1 WSMVD	P	UTU-38420	N2995
BONANZA 1023-7G	07	1005	230E	4304737326	16765		GW	P	SWNE		1 WSMVD	P	UTU-38420	N2995
BONANZA 1023-7A	07	1005	230E	4304737327	16796		GW	P	NENE		1 WSMVD	P	UTU-38420	N2995
BONANZA 1023-70	07	1005	230E	4304738304	16713		GW	P	SWSE		1 MVRD	P	UTU-38420	N2995
BONANZA 1023-70 BONANZA 1023-7B-3	07	1003	230E	4304738912	17016		GW	P	NWNE		1 WSMVD	P	UTU-38420	N2995
		1005	230E				GW	Р	NWSE	-	1 WSMVD	P		N2995
BONANZA 1023-07JT	07			4304739390	16869 17494		GW	P		D		P		N2995
BONANZA 1023-7J2AS	07	100S	230E	4304750474	-					+ +				
BONANZA 1023-7J2DS	07	100\$	230E	4304750475	17495	-	GW	P		D	1 WSMVD	Р		N2995
BONANZA 1023-7L3DS	07	1008	230E	4304750476	17939		GW	Р		D	1 WSMVD	P		N2995
BONANZA 1023-7M2AS	07	1008	230E	4304750477	17942		GW	P	· i	D	1 WSMVD	Р		N2995
BONANZA 1023-7N2AS	07	100S	230E	4304750478	17940		GW	Р		D	1 WSMVD	P		N2995
BONANZA 1023-7N2DS	07	100S	230E	4304750479	17941			P	NWSW	D	1 WSMVD	P		N2995
BONANZA 1023-704S	07	100S	230E	4304750480	17918		GW	P	SESE	D	1 WSMVD	Р		N2995
BONANZA 1023-7P2S	07	100S	230E	4304750482	17919			Р	SESE	D	1 WSMVD	Р		N2995
BONANZA 8-2	08	100S	230E	4304734087	13851	1 (GW	Р	SESE		1 MVRD	Р	U-37355	N2995

BONANZA 8-3	08	100S	230E	4304734770	13843	1 GW	Р	NWNW		1 MVRD	Р	U-37355	N2995
BONANZA 1023-8A	08	100S	230E	4304735718	14932	1 GW	Р	NENE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8L	08	100S	230E	4304735719	14876	1 GW	Р	NWSW		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8N	08	100S	230E	4304735720	15104	1 GW	Р	SESW	Ì	1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8F	08	100S	230E	4304735989	14877	1 GW	S	SENW		1 WSMVD	s	UTU-37355	N2995
BONANZA 1023-8I	08	100S	230E	4304738215	16358	1 GW	Р	NESE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8K	08	100S	230E	4304738216	16354	1 GW	Р	NESW		1 WSMVD	Р		N2995
BONANZA 1023-8M	08	1008	230E	4304738217	16564	1 GW	Р	swsw	1	1 MVRD	Р		N2995
BONANZA 1023-8G	08	100S	230E	4304738218	16903	1 GW	Р	SWNE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8E	08	100S	230E	4304738219	16397	1 GW	Р	SWNW		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8C	08	100S	230E	4304738220	16355	1 GW	Р	NENW		1 WSMVD	Р		N2995
BONANZA 1023-8B	08	100S	230E	4304738221	16292	1 GW	Р	NWNE	+	1 WSMVD	Р		N2995
BONANZA 1023-8H	08	100S	230E	4304738222	16353	1 GW	P	SENE	-	1 WSMVD	P	UTU-37355	N2995
BONANZA 1023-80	08	100S	230E	4304738305	16392	1 GW	Р	SWSE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-8B-4	08	100S	230E	4304738914	17019	1 GW	P	NWNE		1 WSMVD	Р		N2995
BONANZA 1023-8A1DS	08	100S	230E	4304750481	17518	1 GW	P	NENE	D	1 WSMVD	P		N2995
BONANZA 1023-8A4BS	08	100S	230E	4304750483	17519	1 GW	P	NENE	D	1 WSMVD	P		N2995
BONANZA 1023-8B1AS	08	100S	230E	4304750484	17520	1 GW	P	NENE	D	1 WSMVD	Р		N2995
BONANZA 1023-8B2AS	08	1008	230E	4304750485	17521	1 GW	P	NENE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-802S	08	1005	230E	4304750495	17511	1 GW	P	NWSE	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8J1S	08	100S	230E	4304750496	17509	1 GW	P	NWSE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-803S	08	100S	230E	4304750497	17512	1 GW	P	NWSE	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8J3	08	100S	230E	4304750498	17510	1 GW	Р	NWSE	-	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8C4CS	08	100S	230E	4304750499	17544	1 GW	P	NENW	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8D2DS	08	100S	230E	4304750500	17546	1 GW	P	NENW	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8D3DS	08	100S	230E	4304750501	17545	1 GW	P	NENW	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8F3DS	08	100S	230E	4304750502	17543	1 GW	Р	NENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8A4CS	08	100S	230E	4304751131	18169	1 GW	Р	NWNE	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8B3BS	08	100S	230E	4304751132	18167	1 GW	P	NWNE	D	1 WSMVD	P	UTU 37355	N2995
BONANZA 1023-8C1AS	08	100S	230E	4304751133	18166	1 GW	Р	NWNE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8G3AS	08	1005	230E	4304751134	18168	1 GW	P	NWNE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8E2AS	08	100S	230E	4304751135	18227	1 GW	Р	SENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8F3BS	08	100S	230E	4304751136	18227	1 GW	P	SENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8F4AS	08	100S	230E	4304751137	18224	1 GW	Р		D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8F4DS	08	100S	230E	4304751138	18225	1 GW	Р	SENW	D	1 WSMVD	Р		N2995
BONANZA 1023-8J2CS	08	100S	230E	4304751139	18226	1 GW	Р	SENW	D	1 WSMVD	Р		N2995
BONANZA 1023-8G4DS	08	1005	230E	4304751140	18144	1 GW	P	NESE	D	1 WSMVD	P		N2995
BONANZA 1023-8H2DS	08		230E	4304751141	18142		P	NESE	D	1 WSMVD	1 -	UTU 37355	
BONANZA 1023-8H3DS	08		230E	4304751142	18143	1 GW	P	NESE	D	1 WSMVD	Р		N2995
BONANZA 1023-8H4DS	08	100S	230E	4304751143	18141	1 GW	P	NESE	D	1 WSMVD	Р	NAME OF THE OWNER OWNER O	N2995
BONANZA 1023-814BS	08		230E	4304751144	18155	1 GW	P	NESE	D	1 WSMVD	P		N2995
BONANZA 1023-8J4BS	08	1005	230E	4304751145	18154	1 GW	P	NESE	D	1 WSMVD	P		N2995
BONANZA 1023-891AS	08	1005	230E	4304751146	18156	1 GW	P	NESE	D	1 WSMVD	P		N2995
BONANZA 1023-8P2BS	08	1	230E	4304751147	18153	1 GW	P	NESE	D	1 WSMVD	P		N2995
BONANZA 1023-8P4AS	08		230E	4304751148	18157	1 GW	P	NESE	D	1 WSMVD	P		N2995
BONANZA 1023-8E2DS	08		230E	4304751149	18201	1 GW	P		D	1 WSMVD	P	UTU 37355	
55.44 (14E) 1 10E0-0EED0		, 555									; •	0.000	

			1					1_	1	T	T	1		1.10
BONANZA 1023-8E3DS	80	100S	230E	4304751150	18200	1 0		Р	NWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8K1CS	80	100S	230E	4304751151	18199	1 0		Р	NWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8K4CS	08	100S	230E	4304751152	18198	1 0		Р	NWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8L3DS	80	100S	230E	4304751153	18197	1 0		Р	NWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8M2AS	80	100S	230E	4304751154	18217	1 0		Р	swsw	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8M2DS	80	100S	230E	4304751155	18216	1 0		Р	SWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8N2BS	80	100S	230E	4304751156	18218	1 0		Р	SWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-803CS	80	100S	230E	4304751157	18254	1 0		Р	SWSE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8N3DS	80	100S	230E	4304751158	18215		W	Р	SWSW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-804AS	08	100S	230E	4304751159	18252	1 G		Р	SWSE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8P2CS	08	100S	230E	4304751160	18251	1 G		Р	SWSE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-8P3CS	08	100S	230E	4304751161	18253	1 G		Р	SWSE	D	1 WSMVD	Р	UTU 37355	N2995
CANYON FEDERAL 2-9	09	100S	230E	4304731504	1468	1 G		Р	NENW	1	1 MVRD	Р	U-37355	N2995
SOUTHMAN CANYON 9-3-M	09	100S	230E	4304732540	11767	1 G		S	SWSW		1 MVRD	S	UTU-37355	N2995
SOUTHMAN CANYON 9-4-J	09	100S	230E	4304732541	11685	1 G		S	NWSE		1 MVRD	S	UTU-37355	N2995
BONANZA 9-6	09	100S	230E	4304734771	13852	1 G		P	NWNE		1 MVRD	Р	U-37355	N2995
BONANZA 9-5	09	100S	230E	4304734866	13892	1 G	W	Р	SESW		1 MVRD	Р	U-37355	N2995
BONANZA 1023-9E	09	100S	230E	4304735620	14931	1 G		Р	SWNW		1 WSMVD	Р	U-37355	N2995
BONANZA 1023-9I	09	100S	230E	4304738223	16766	1 G	W	Р	NESE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-9D	09	100S	230E	4304738306	16398	1 G	W	Р	NWNW		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-9J	09	100S	230E	4304738811	16989	1 G		Р	NWSE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-9B3BS	09	100S	230E	4304750503	17965	1 G	W	Р	SENE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-9B3CS	09	100S	230E	4304750504	17968	1 G	W	Р	SENE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-9H2BS	09	100S	230E	4304750505	17966	1 G	W	Р	SENE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-9H2CS	09	100S	230E	4304750506	17967	1 G	W	Р	SENE	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 10-2	10	100S	230E	4304734704	13782	1 G	W	Р	NWNW		1 MVRD	Р	U-72028	N2995
BONANZA 1023-10L	10	100S	230E	4304735660	15164	1 G	W	Р	NWSW		1 WSMVD	Р	U-38261	N2995
BONANZA 1023-10E	10	100S	230E	4304738224	16501	1 G	W	Р	SWNW		1 MVRD	Р	UTU-72028	N2995
BONANZA 1023-10C	10	100S	230E	4304738228	16500	1 G	W	Р	NENW		1 MVRD	Р	UTU-72028	N2995
BONANZA 1023-10C-4	10	100S	230E	4304738915	17015	1 G	W	Р	NENW		1 MVRD	Р	UTU-72028	N2995
BONANZA 11-2 😾	11	100S	230E	4304734773	13768	1 G	W	Р	SWNW		1 MVMCS	Р	UTU-38425	N2995
BONANZA 1023-11K	11	100S	230E	4304735631	15132	1 G	W	Р	NESW		1 WSMVD	Р	UTU-38425	N2995
BONANZA 1023-11B	11	100S	230E	4304738230	16764	1 G	W	Р	NWNE		1 MVRD	Р	UTU-38425	N2995
BONANZA 1023-11F	11	100S	230E	4304738232	16797	1 G	W	Р	SENW		1 MVRD	Р	UTU-38425	N2995
BONANZA 1023-11D	11	100S	230E	4304738233	16711	1 G	W	Р	NWNW		1 MVRD	Р	UTU-38425	N2995
BONANZA 1023-11G	11	100S	230E	4304738235	16826	1 G	W	Р	SWNE		1 MVRD	Р	UTU-38425	N2995
BONANZA 1023-11C	11	100S	230E	4304738309	16736	1 G	W	Р	NENW		1 MVRD	Р	UTU-38425	N2995
BONANZA 1023-11J	11	100S	230E	4304738310	16839	1 G	W	Р	NWSE		1 WSMVD	Р	UTU-38424	N2995
BONANZA 1023-11N	11	100S	230E	4304738311	16646	1 G	W	Р	SESW		1 MVRD	Р	UTU-38424	N2995
BONANZA 1023-11M	11	100S	230E	4304738312	16687	1 G		Р	SWSW		1 MVRD	Р	UTU-38424	N2995
BONANZA 1023-11L	11	100S	230E	4304738812	16987	1 G	W	Р	NWSW		1 WSMVD	Р	UTU-38424	N2995
NSO FEDERAL 1-12	12	100S	230E	4304730560	1480	1 G		Р	NENW		1 MVRD	Р		N2995
WHITE RIVER 1-14	14	100S	230E	4304730481	1500	1 G		S	NENW		1 MVRD	S	U-38427	N2995
BONANZA 1023-14D	14	100S	230E	4304737030	16799	1 G		P	NWNW		1 MVRD	Р		N2995
BONANZA 1023-14C	14		230E	4304738299	16623	1 G		P	NENW			P		N2995
BONANZA FEDERAL 3-15	15	1008	230E	4304731278	8406	1 G	_	Р	NENW			Р	U-38428	N2995
DOIVAIVEAT EDETIVIE 0-10		1.550						•	1	<u> </u>		<u> </u>	,	

* not moved into unit

BONANZA 1023-15H	15	100S	230E	4304738316	16688		1 GW	Р	SENE		1 MVRD	Р	UTU-38427	N2995
BONANZA 1023-15J	15	100S	230E	4304738817	16988	,	1 GW	Р	NWSE		1 MVRD	Р	UTU-38427	N2995
BONANZA 1023-15H4CS	15	100S	230E	4304750741	17492		1 GW	Р	NESE	D	1 MVRD	Р	UTU 38427	N2995
BONANZA 1023-15I2AS	15	100S	230E	4304750742	17493		1 GW	Р	NESE	D	1 WSMVD	Р	UTU 38427	N2995
BONANZA 1023-15I4BS	15	100S	230E	4304750743	17490		1 GW	Р	NESE	D	1 WSMVD	Р	UTU 38427	N2995
BONANZA 1023-15P1BS	15	100S	230E	4304750744	17491		I GW	Р	NESE	D	1 WSMVD	Р	UTU 38427	N2995
LOOKOUT POINT STATE 1-16	16	100S	230E	4304730544	1495	3	GW	Р	NESE		3 WSMVD	Р	ML-22186-A	N2995
BONANZA 1023-16J	16	100S	230E	4304737092	15987		GW	OPS	NWSE		3 WSMVD	OPS	ML-22186-A	N2995
BONANZA 1023-17B	17	100S	230E	4304735747	15165		I GW	Р	NWNE		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-17C	17	100S	230E	4304738237	16585		I GW	Р	NENW		1 WSMVD	Р	UTU-37355	N2995
BONANZA 1023-17D3S	17	100S	230E	4304750511	17943		GW	Р	NENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-17E2S	17	100S	230E	4304750512	17944		GW	Р	NENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-17E3AS	17	100S	230E	4304750513	17945	1	GW	Р	NENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-17E3CS	17	100S	230E	4304750514	17946	1	GW	Р	NENW	D	1 WSMVD	Р	UTU 37355	N2995
BONANZA 1023-18G	18	100S	230E	4304735621	14410	•	GW	Р	SWNE		1 WSMVD	Р	U-38241	N2995
BONANZA 1023-18B	18	100S	230E	4304735721	14395		GW	Р	NWNE		1 WSMVD	Р	U-38421	N2995
BONANZA 1023-18DX (RIGSKID)	18	100S	230E	4304736218	14668	1	GW	Р	NWNW		1 WSMVD	Р	U-38241	N2995
BONANZA 1023-18A	18	100S	230E	4304738243	16625	1	GW	Р	NENE		1 WSMVD	Р	UTU-38421	N2995
BONANZA 1023-18F	18	100S	230E	4304738244	16624	1	GW	Р	SENW		1 WSMVD	Р	UTU-38421	N2995
BONANZA 1023-18E	18	100S	230E	4304738245	16645	1	GW	Р	SWNW		1 MVRD	Р	UTU-38421	N2995
BONANZA 1023-18C	18	100S	230E	4304738246	16734	1	GW	Р	NENW		1 MVRD	Р	UTU-38421	N2995
BONANZA 1023-18G-1	18	100S	230E	4304738916	17135	1	GW	Р	SWNE		1 WSMVD	Р	UTU-38421	N2995
BONANZA 1023-18D3AS	18	100S	230E	4304750448	17498	. 1	GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18D3DS	18	100S	230E	4304750449	17499	1	GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18E2DS	18	100S	230E	4304750450	17497	1	GW	Р	SWNW	D	1 WSMVD	P	UTU 38421	N2995
BONANZA 1023-18E3AS	18	100S	230E	4304750451	17496	1	GW	Р	SENW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18L2S	18	100S	230E	4304750520	18111		GW	P	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18L3S	18	100S	230E	4304750521	18110	1	GW	P	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18K3AS	18	100S	230E	4304751061	18112	1	GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18K3BS	18	100S	230E	4304751063	18113	1	GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18M2AS	18	100S	230E	4304751064	18117	1	GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18M2DS	18	100S	230E	4304751065	18116	1	GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18N2AS	18	100S	230E	4304751066	18114		GW	Р	SWNW	D	1 WSMVD	Р	UTU 38421	N2995
BONANZA 1023-18N2DS	18	100S	230E	4304751067	18115	1	GW	Р	SWNW	D	1 WSMVD	P	UTU 38421	N2995
BONANZA 1023-10F	10	100S	230E	4304738225	16565		GW	Р	SENW		MVRD	Ρ	UTU 72028	N2995
BONANZA 1023-6D1AS	6	100S	230E	4304751450	18320		GW	Р	NENW	D	WSMVD	P	UTU 38419	N2995
BONANZA 1023-6C1CS	6	100S	230E	4304751448	18319		GW		NENW	D			UTU 38419	N2995
BONANZA 1023-6D3AS	6	100S	230E	4304751452	18317		GW	Р	NENW	D	WSMVD	Р	UTU 38419	N2995



State of Utah DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER

Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

September 4, 2014

CERTIFIED MAIL NO.: 7011 2970 0001 8828 1634

Mr. Andy Lytle Kerr-McGee Oil and Gas Onshore 1099 18TH Street Denver, CO 80202 43 047 35162 Poneunza 1023-20 2 105 23E

Subject: Extended Shut-in and Temporary Abandoned Well Requirements for Fee or State Leases

Dear Mr. Lytle:

As of April 2014, Kerr-McGee Oil and Gas Onshore (Kerr-McGee) has nineteen (19) State Lease Wells and one (1) Fee Lease Well (see attachment A) that are currently in non-compliance with the requirements for extended shut-in or temporarily abandoned (SI/TA) status. Thirteen (13) wells were added to Kerr-McGee's SI/TA list in 2014.

Seven (7) of these wells (attachment A) have previously been issued notices of non-compliance and have remained in non-compliance. Three (3) of these wells (attachment A) have been shut-in beyond five (5) years and are cause for concern due to unknown status of well integrity. The Division acknowledges that Kerr-McGee has plans to plug two (2) of the wells listed (attachment A) and has approved plugging procedures.

Kerr-McGee shall submit plans for each well stating which wells will be plugged with accompanying procedures, placed back on production, or requesting SI/TA extension with proof of wellbore integrity and good cause for such request. All wells need an individual sundry filed and are required to meet the SI/TA rules as listed below.



Page 2 Kerr-McGee Oil and Gas Onshore September 4, 2014

Wells SI/TA beyond twelve (12) consecutive months requires filing a Sundry Notice (R649-3-36-1). Wells with five (5) years non-activity or non-productivity shall be plugged, unless the Division grants approval for extended shut-in time upon a showing of good cause by the operator (649-3-36-1.3.3). For extended SI/TA consideration the operator shall provide the Utah Division of Oil, Gas & Mining with the following:

- 1. Reasons for SI/TA of the well (R649-3-36-1.1)
- 2. The length of time the well is expected to be SI/TA (R649-3-36-1.2), and
- 3. An explanation and supporting data if necessary, for showing the well has integrity, meaning that the casing, cement, equipment condition, static fluid level, pressure, existence or absence of Underground Sources of Drinking Water and other factors do not make the well a risk to public health and safety or the environment (R649-3-36-1.3).

Please note that the Divisions preferred method for showing well integrity is by MIT

Submitting the information suggested below may help show well integrity and may help qualify your well for extended SI/TA. Note: As of July 1, 2003, wells in violation of the SI/TA rule R649-3-36 may be subject to full cost bonding (R649-3-1-4.2, 4.3).

- 1. Wellbore diagram, and
- 2. Copy of recent casing pressure test, and
- 3. Current pressures on the wellbore (tubing pressure, casing pressure, and casing/casing annuli pressure) showing wellbore has integrity, and
- 4. Fluid level in the wellbore, and
- 5. An explanation of how the submitted information proves integrity.

If the required information is not received within 30 days of the date of this notice, further actions may be initiated. If you have any questions concerning this matter, please contact me at (801) 538-5281.

Sincerely

Dustin K. Doucet Petroleum Engineer

DKD/JP/js
cc: Compliance File
Well File
LaVonne Garrison, SITLA
N:\O&G Reviewed Docs\ChronFile\PetroleumEngineer\SITA

ATTACHMENT A

	Well Name	API	LEASE	Years Inactive	Prior Notice
1	BONANZA 1023-16J	43-047-37092	ML-22186-A	7 years 1 month	2 ND NOTICE
2	NBU 921-34L	43-047-36388	STUO-1194-A	5 years	2 ND NOTICE
3	CIGE 79D	43-047-30896	ML-23612	4 years 4 months	2 ND NOTICE
4	NBU 921-33J (will PA 6/2/14)	43-047-36394	STUO-015630	5 years 2 months	2 ND NOTICE
5	CIGE 3-32-9-22	43-047-30320	ML-22649	3 years 11 months	1 ST NOTICE
6	NBU 31-12B	43-047-30385	ML-01197-A	2 years 10 months	1 ST NOTICE
7	NBU 69N2	43-047-31090	U-01194-ST	3 years 3 months	1 ST NOTICE
8	BONANZA 1023-20	43-047-35662	ML-47062	1 year 1 month	
9	CIGE 140	43-047-31977	ML-10755	1 year	
10	CIGE 224	43-047-32883	ML-2252	1 year	
11	CIGE 239	43-047-33206	ML-22582	1 year 6 months	
12	CIGE 284	43-047-34792	ML-23612	1 year 2 months	
13	CIGE 5	43-047-30335	U01207A-ST	1 year 3 months	
14	HALL ET AL 31 18	43-047-30664	FEE	1 year 1 month	
15	MORGAN STATE 13-36	43-047-32817	ML-22265	1 year 11 months	
16	NBU 1021-16G	43-047-35111	ML-10755	1 year 4 months	
17	NBU 562-19E (will PA 5/23/14)	43-047-37536	ML-22792	1 year	
18	STATE 1022-32I	43-047-35648	ML-22798	1 year 2 months	
19	TRIBAL 31-60	43-047-33340	ML-28048	1 year 2 months	
20	WONSITS ST 2-32	43-047-32819	ML-47780	1 year	

	STATE OF UTAH		FORM 9
ı	DEPARTMENT OF NATURAL RESOUR DIVISION OF OIL, GAS, AND MII		5.LEASE DESIGNATION AND SERIAL NUMBER: ML-47062
SUNDR	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	posals to drill new wells, significantly reenter plugged wells, or to drill horizon n for such proposals.		7.UNIT or CA AGREEMENT NAME: PONDEROSA
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: BONANZA 1023-20
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ON	ISHORE, L.P.		9. API NUMBER: 43047356620000
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th	h Street, Suite 600, Denver, CO, 8021	PHONE NUMBER: 7 3779 720 929-	9. FIELD and POOL or WILDCAT: 110ATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0865 FSL 1947 FEL			COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 02 Township: 10.0S Range: 23.0E Merio	dian: S	STATE: UTAH
11. CHECI	K APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION
4/25/2014	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
SPUD REPORT	✓ PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION
,	WILDOAT WELL DETERMINATION	OTHER	OTHER:
	WILDCAT WELL DETERMINATION	□ OTHER	<u> </u>
THE SUBJECT WE REFERENCE TO UD FOR EXTENDED	COMPLETED OPERATIONS. Clearly show ELL WAS RETURNED TO PRO POGM NON COMPLIANCE LE D SHUT-IN AND TEMPORARY UIREMENTS FOR FEE OR STAT	ODUCTION 04/25/2014. TTER DATED 09/04/2014 ABANDONED WELL	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY October 06, 2014
NAME (PLEASE PRINT) Doreen Green	PHONE NUMB 435 781-9758	BER TITLE Regulatory Analyst II	
SIGNATURE N/A		DATE 10/3/2014	

P.O. Box 173779 • DENVER, CO 80202-3779



October 2, 2014

OCT 09 2014

State of Utah Division of Oil, Gas and Mining 1594 West North Temple Ste. 1210 Salt Lake City, UT 84116 DIV. OF OIL, GAS & MINING

ATTENTION:

Dustin Doucet

RE:

Extended Shut-in and Temporarily Abandoned Well Requirements for Fee or State Leases- UDOGM letter dated September 4, 2014

Dear Mr. Doucet,

We are in receipt of your letter dated September 4, 2014 regarding the shut-in and temporarily abandoned status of wells operated by Kerr-McGee Oil and Gas Onshore. All required sundry notices have been filed as requested in the letter. Some wells documented in the letter previously had Plug and Abandonment procedures and notice of intent sundry notices submitted. Anadarko intends to Plug and Abandon the applicable wells by the end of the first quarter-2015.

The attached list explains the current well statuses and go forward plans for each well documented in the September 4, 2014 letter.

Should you have any additional questions or concerns, please don't hesitate to contact me direct at (720) 929-6100 or via email at andy.lytle@anadarko.com.

Sincerely,

Andy Lytle

Regulatory Supervisor

WELL NAME	APL	LEASE	YEARS INACTIVE	PRIOR NOTICE	COMMENTS
BONANZA 1023-16J	4304737092	ML22186A	7 YEARS 1 MONTH	2ND NOTICE	PA NOI Sundry submitted 10/03/2014.
NBU 921-34L	4304736388	STUO1194A	5 YEARS	2ND NOTICE	Sundry submitted 09/16/2014 for the conversion to a monitor well (Not previously reported in 2012) and yearly status for a monitor well.
CIGE 79D	4304730896	ML23612	4 YEARS 4 MONTHS	2ND NOTICE	Sundry submitted 09/16/2014, yearly status for a monitor well.
NBU 921-33J	4304736394	STU0015630	5 YEARS 2 MONTHS	2ND NOTICE	PA Sundry approved 07/09/2014, on rig schedule for week of October 6-2014.
CIGE 3-32-9-22	4304730320	ML22649	3 YEARS 11 MONTHS	1ST NOTICE	PA Sundry approved 08/07/2012, on rig schedule for week of October 6-2014.
NBU 31-12B	4304730385	ML01197A	2 YEARS 10 MONTHS	1ST NOTICE	PA Sundry approved 07/23/2013, on rig schedule for week of October 6-2014.
NBU 69N2	4304731090	U01194ST	3 YEARS 3 MONTHS	1ST NOTICE	PA NOI Sundry submitted 10/03/2014.
BONANZA 1023-20	4304735662	ML47062	1 YEAR 1 MONTH		Return to Production sundry submitted 10/03/2014. Producing since 04/25/2014, production accounting has been reporting production to UDOGM as of April 2014.
CIGE 140	4304731977	ML10755	1 YEAR		PA NOI Sundry submitted 10/02/2014.
CIGE 224	4304732883	ML2252	1 YEAR		PA NOI Sundry submitted 10/01/2014.
CIGE 239	4304733206	ML22582	1 YEAR 6 MONTHS		Return to Production sundry submitted 10/03/2014. Producing since 06/14/2014, production accounting has been reporting production to UDOGM as of June 2014.
CIGE 284	4304734792	ML23612	1 YEAR 2 MONTHS		Return to Production sundry submitted 10/03/2014. Producing since 03/29/2014, production accounting has been reporting production to UDOGM as of March 2014.
CIGE 5	4304730335	U01207AST	1 YEAR 3 MONTHS		Sundry submitted 10/03/2014. This well is currently surface commingled with the NBU 922-31JT-1T meter. The well was mistakenly made in-active, therefore production was not allocating. The well has been made active and is presently allocating. 12/17/2009 a sundry for surface commingling was approved by UDOGM.
HALL ET AL 31 18	4304730664	FEE	1 YEAR 1 MONTH		PA NOI Sundry submitted 09/30/2014.
MORGAN STATE 13-36	4304732817	ML22265	1 YEAR 11 MONTHS		PA NOI Sundry submitted 09/30/2014.
NBU 1021-16G	4304735111	ML10755	1 YEAR 4 MONTHS		PA NOI Sundry submitted 10/03/2014.
NBU 562-19E	4304737536	ML22792	1 YEAR		PA Sundry approved 07/09/2014, on rig schedule for week of October 6-2014.
STATE 1022-32I	4304735648	ML22798	1 YEAR 2 MONTHS		PA NOI Sundry submitted 09/30/2014.
TRIBAL 31-60	4304733340	ML28048	1 YEAR 2 MONTHS		Return to Production sundry submitted 10/03/2014. A new meter installed 09/30/2014, well is currently intermitting.
WONSITS ST 2-32	4304732819	ML47780	1 YEAR		PA NOI Sundry submitted 10/01/2014.

			FORM 9
	STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES	3	
	DIVISION OF OIL, GAS, AND MININ		5.LEASE DESIGNATION AND SERIAL NUMBER: ML-47062
SUNDF	RY NOTICES AND REPORTS O	N WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	oposals to drill new wells, significantly de reenter plugged wells, or to drill horizonta n for such proposals.		7.UNIT or CA AGREEMENT NAME: PONDEROSA
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: BONANZA 1023-20
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ON	NSHORE, L.P.		9. API NUMBER: 43047356620000
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18tl	P h Street, Suite 600, Denver, CO, 80217 3	HONE NUMBER: 720 929-	9. FIELD and POOL or WILDCAT: 45ATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0865 FSL 1947 FEL			COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 02 Township: 10.0S Range: 23.0E Meridiai	n: S	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
7/7/2016	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	New construction
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
		RECLAMATION OF WELL SITE	
SPUD REPORT Date of Spud:	PRODUCTION START OR RESUME	1	☐ RECOMPLETE DIFFERENT FORMATION
Date of Spau.	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON
	L TUBING REPAIR	│ VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION
	WILDCAT WELL DETERMINATION	OTHER	OTHER:
I .	COMPLETED OPERATIONS. Clearly show all		
	Gas Onshore, LP respectfully		proved by the hh Division of
	ne BONANZA 1023-2O(single) ed procedure for details. Thar	Woll. I loade	Gas and Mining
See the attach	ed procedure for details. That	lu you.	ly 28, 2016
		Date:	1 0
		By:	lot K Junt
			· ·
		nı n	
		Please Rev	iew Attached Conditions of Approval
NAME (PLEASE PRINT) Candice Barber	PHONE NUMBER 435 781-9749	R TITLE HSE Representative	
SIGNATURE		DATE	
N/A		7/7/2016	

RECEIVED: Jul. 07, 2016



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Sundry Conditions of Approval Well Number 43047356620000

- 1. Notify the Division at least 24 hours prior to conducting abandonment operations. Please call Dan Jarvis at 801-538-5338.
 - 2. Amend Plug #3: Plug shall be balanced from ±3305' to 2528'.
- 3. Amend Plug #5: Establish circulation down the 4 $\frac{1}{2}$ " casing back up the 4 $\frac{1}{2}$ " x 9 5/8" annulus. If injection into the perfs cannot be established a 250' plug (±20 sx) shall be balanced from ±1131' to 881'. If injection is established: RIH with CICR and set @ 1031' (50' above perfs). M&P 74 sx cement, sting into CICR pump 63 sx, sting out and dump 12 sx on top of CICR.
 - 4. All balanced plugs shall be tagged to ensure that they are at the depth specified.
 - 5. All annuli shall be cemented from a minimum depth of 100' to the surface.
 - 6. Surface reclamation shall be done in accordance with R649-3-34 Well Site Restoration.
 - 7. All requirements in the Oil and Gas Conservation General Rule R649-3-24 shall apply.
- 8. If there are any changes to the procedure or the wellbore configuration, notify Dustin Doucet at 801-538-5281 (ofc) or 801-733-0983 (home) prior to continuing with the procedure.
- 9. All other requirements for notice and reporting in the Oil and Gas Conservation General Rules shall apply.

RECEIVED: Jul. 28, 2016

7/28/2016			Wellbo	re Dia	gram				r263
API Well	No: 43-047-35662-00	0-00 Permit	No:		Well Nam	e/No: BON	ANZA 1023	-20	
Company	Name: KERR-MCC	GEE OIL & GAS	ONSHORE,	L.P.					
Location:	Sec: 2 T: 10S R: 23	E Spot: SWSE	9	String Info	rmation				620
Coordina	tes: X: 645860 Y: 44	126171		C4	Bottom	Diameter	Weight	_	Cap.
Field Nan	ne: NATURAL BUT	TES		String HOL1	(ft sub) 40	(inches) 20	(lb/ft)	(ft)	GT/
County N	ame: UINTAH				40	14	54	40	
•		7154 A		HOL2	1900	12.25	J4	40	
П	Cement from 40 ft. fo	1001 = 85%		SURF	1900	9.625	32.3	1900	
	ol ar	1001/11/5830	· 17)=295	CHOL3	7955	7.875	32,3	1700	
	Cement from 40 ft. to	surface	32 de	MPROD	7955	4.5	11.6	7955	11.45
HWIN	Conductor: 14 in. @	40 ft.	(379210	71	7391	2.375	11.0	1755	(1.1)
"MANA"	Hole: 20 in. @ 40 ft.			•			L 11		1 -
, <mark> </mark>		Plu #5			93	18" x 4	12"		1 5.
4 7	welon I	Ply \$5							
RV	(M)	1000	X (15)	3017) = 5	585K				
	Cement from 1900 ft. to	o surface 0 + 200	10/1/6/5	(U-459):	125/		. ا ا	/	
75'	Cement from 1900 ft. to Surface: 9.625 in. @ 19	900 ft. About	11		745x to	stal toca	2881 Vo	2	
ه د	Hole: 12.25 in. @ 1900	n. Plug 4	9	Cement In	formation	•		31.77	
* X	2	\$54=105			BOC	TOC			
1-1-1-1	(940 [*]			String	(ft sub)	(ft sub)	Class	Sacks	
1111		TOCE	2 1835	COND	40	0	UK	28	
			Van	PROD	7955	1475	HS	350	
,	2528			PROD	7955	1475	50	1450	
46 111				SURF	1900	0	UK	580	
CZ W	* PlugI	\$ 3							
45 C M			1.22.						
I XIII	(5424)(1,15	1)(11,459)=	777	ગ્રા					
· MI	set @3305	#3 5)(11.459)= 1 5' to Too	E150	o Perforatio	n Informat	ion			
00' -			,	Тор	Bottom	1011			
45640/1-1-3	30 2			(ft sub)	(ft sub)	Shts	Ft No SI	nts Dt Squ	eeze
1111				5330	5491				
1111	-1 De	42		6154	7766				
H-H-	1833 PLJ	1							
	111 e.	(1,15)(11,459)	2 510,						
7'-1	1 ((4.26-)		toce ?) X ' 4 ' 2					
7 - 4	013		1	,0,5					
7 - 4	a13			VON	_				
7 - 1	(80))lug# 1		Von	-				
7 - 1	180' (1856))lug#1		Formation	Informati	on			
7 - 7 4	180' (856) 180' (856))(10g# 1	() = pc	Formation Formation	Informati	on			
7 - 7 5	180' (85%) BPC 5285' (85%))([1])([14])(Tace	1) = 1051 25181	Formation Formation UNTA	Information Depth	on			
7 - 1 5 0	180' 180' 180' 180' 180' 180' 180' 180')(1,17)(11.45°	1) = 1051 = 51801	Formation Formation UNTA GRRV	Informati on Depth 0 979	on			
	18833' PLJO 180' (1656) 1806 5285' (856 15491' 1518P@5871')([17](11.45°) Toce	1) = 1051 251801 Vol	TAKCK	2040	on			
	CIBP C 5871		1) = 105 1 2 51801 VSV	BMSW	3200	on			
	CIBP C 5871		1) = 105' 5180' VSU	BMSW WSTC	3200 4027	on			
	Cement from 7955 ft. to County 24. Tubing: 2.375 in. @ 739	1475 ft. 1 ft.	1) = 1051 251801 VSV	BMSW	3200	on			
, /	Cement from 7955 ft. to Care Tubing: 2.375 in. @ 739 Production: 4.5 in. @ 79	1475 ft. 1 ft.	1) = 1051 251801 VSV	BMSW WSTC	3200 4027	on			
	Cement from 7955 ft. to County 24. Tubing: 2.375 in. @ 739	1475 ft. 1 ft. 155 ft.	1) = 105 1 2 5180' V3 11	BMSW WSTC	3200 4027	on			

BONANZA 1023-20 865' FSL & 1947' FEL SWSE SEC. 2, T10S, R23E UINTAH UT

 KBE:
 5461'
 API NUMBER:
 4304735662

 GLE:
 5457'
 LEASE NUMBER:
 ML-47062

TD: 7955' **LAT/LONG:** 39.97305/-109.291797

PBTD: 7911'

CASING: 12.25" HOLE

SURFACE 9.625" 32.3# H-40 @ 1888'

7.875" HOLE

PRODUCTION 4.5" 11.6# I-80 @ 7936'

Est. TOC @ 1475' CBL

PERFORATIONS: WASATCH-MESAVERDE TOP-BOTTOM 5335'-7771'

TUBING: 2.375" 4.7# J-55 TUBING @ 7375'

Tubular/Borehole	ID	Drift	Collapse	Burst	Capacities					
Tubulal/ Borellole	inches	inches	psi	psi	Gal./ft.	Cuft/ft.	Bbl./ft.			
2.375" 4.7# J-55 tbg	1.995	1.901	8100	7700	0.1624	0.02171	0.00387			
2.375" 4.7# P-110 tbg	1.995	1.901	13800	15400	0.1624	0.02171	0.00387			
2.375" 4.7# L-80 tbg	1.995	1.901	11780	11200	0.1624	0.02171	0.00387			
4.5" 11.6# I-80 csg	4	3.875	6350	7780	0.65282	0.08727	0.01554			
9.625" 32.3# H-40 csg	9.001	8.845	1400	2270	3.30549	0.44188	0.0787			

Annular Capacities	Gal./ft.	Cuft/ft.	Bbl./ft.
2.375" tbg. X 4.5" csg		0.05651	
4.5" csg. X 9.625" csg	2.47927	0.33143	0.05903
4.5" csg X 7.875 borehole	1.70406	0.2278	0.04057

GEOLOGIC INFORMATION:

Formation Depth to top, ft.

Uinta Surface
Top Green River 979'
Top Mahogany 1889'
Base Parachute 2646'
Top Wasatch 4043'
Top Mesaverde 5871'

http://digitallibrary.utah.gov/awweb/awarchive?type=file&item=55737

BMSW Elevation ~2261' MSL BMSW Depth ~3200'

1

BONANZA 1023-20 PLUG & ABANDONMENT PROCEDURE

GENERAL

- H2S MAY BE PRESENT. CHECK FOR H2S AND TAKE APPROPRIATE PRECAUTIONS.
- BLOW DOWN BRADEN HEAD AND SURFACE CASING AS NEEDED AS PER SOP.
- CEMENT QUANTITIES BELOW ASSUME NEAT CLASS G, 15.8ppg, YIELD 1.145 CUFT/SX. IF A
 DIFFERENT PRODUCT IS USED, WELLSITE PERSONNEL ARE RESONSIBLE FOR CORRECTING
 QUANTITIES TO YIELD THE STATED SLURRY VOLUME.
- TREATED FRESH WATER WILL BE PLACED BETWEEN ALL PLUGS INSTEAD OF BRINE.
- ALL DISPLACEMENT FLUID SHALL CONTAIN CORROSION INHIBITOR AND BIOCIDE. PREMIX 5 GALLONS PER 100 BBLS FLUID AND IS TO BE PLACED BETWEEN ALL PLUGS.
- NOTIFY APPROPRIATE AGENCY 48 HOURS BEFORE MOVING ON LOCATION.

PERTINENT WELL HISTORY: SEAT NIPPLE. @ 7390' (TUBING PERFORATED @ 7097 to 7103' NO WORK OVER SIUNCE COMPLETION DECEMBER 2004)

PROCEDURE

Note: Approx. 202 SXS Class "G" cement needed for procedure & (2) 4.5" CIBP

Note: YES GYRO ON RECORD. (IF GYRO NEEDED, A GPS READING WILL NEED TO BE TAKEN AT THE WELL SITE AND RECORDED IN OPENWELLS. PLEASE TAKE IT TO THE 6TH DECIMAL PLACE).


- 1. MIRU. KILL WELL AS NEEDED. ND WH, NU AND TEST BOPE.
- 2. POOH W/ TBG & L/D SAME. RU WIRELINE AND MAKE A GAUGE RING RUN TO CHECK FOR FILL PER FOREMAN DISCRETION.
- 3. ISOLATE MESAVERDE PERFORATIONS (> 5871'): RIH ON WIRELINE W/ 4.5" CIBP. SET @ ~ 5871 '. RELEASE CIBP.
- 4. ISOLATE PERFORATIONS (7771'-5335'): RIH ON WIRELINE OR TUBING W/ 4.5" CIBP. SET @ ~5285', (50' above top perf at 5335'). RELEASE CIBP, PUH 10', CIRC ENTIRE HOLE W/ TREATED FRESH WATER AND PRESSURE TEST CASING. SET A 105FT BALANCED CMT PLUG F/ 5285' to 5180'(8 SXS, 9.16 FT3, 1.64 BBLS).
- PROTECT WASATCH TOP (4043'): PUH WITH TUBING AND PUMP A MINIMUM OF (210FT) CMT F/ 4043' to 3833' (16 SXS, 18.32 FT3, 3.27 BBLS).
- 6. PROTECT BMSW AND PARACHUTE BASE (3200', 2646'): PUH WITH TUBING AND PUMP A MINIMUM OF (774FT) CMT F/ 3305' to 3541' (59 SXS, 67.56 FT3, 12.06 BBLS).
- 7. PROTECT CASING SHOE (1888'): PUH WITH TUBING AND PUMP A MINIMUM OF (105FT) CMT F/ 1940.5' to 1835.5' (8 SXS, 9.16 FT3, 1.64 BBLS).
- 8. PROTECT GREEN RIVER (979'): POOH AND RIG UP WIRELINE. RIH WITH PERF GUNS FOR PRODUCTION CASING. PERFORATE CASING AT ~1080.5' (TOC @ ~1475'). PUMP A MINIMUM OF (203FT) CMT F/ 1080.5' to 877.5' WITH A CEMENT RETAINER AT 1801' (58 SXS, 66.41 FT3, 11.83 BBLS). UNSTING AND PUMP A MINIMUM OF (203FT) CMT F/ 1080.5' to 877.5' IN THE PRODUCTION CASING (16 SXS, 18.32 FT3, 3.27 BBLS).
- 9. PROTECT SURFACE (102'): POOH AND RIG UP WIRELINE. RIH WITH PERF GUNS FOR PRODUCTION CASING. PERFORATE CASING AT ~102' (TOC @ ~1475'). PUMP A MINIMUM OF (37 SXS, 42.37 FT3, 7.55 BBLS) CMT TO FILL PRODUCTION CASING AND ANNULUS FROM 102' TO SURFACE.
- 10. CUT OFF WELLHEAD AND INSTALL MARKER PER REGULATIONS.
- 11. RDMO. TURN OVER TO OPERATIONS FOR SURFACE REHAB. SURFACE RECLAMATION TO BE PERFORMED IN ACCORDANCE TO REGULATIONS.

2

BONANZA 1023-20

Total SXS: 202, Total CIBP: 2

<- Plug for Surface at 0' from 0' to 102' with 37SXS,102ft.



- <- Plug for GreenRiver at 979' from 1080.5' to 877.5' with 74SXS,203ft.
- <- TOC at 1475'
- <- Plug for Surface Shoe at 1888' from 1940.5' to 1835.5' with 8SXS,105ft. <- Mahogany at 1889'
- <- Plug for Parachute Base and BMSW at 2646', 3200' from 3305' to 2541' with 59SXS,774ft.
- <- Plug for Wasatch at 4043' from 4043' to 3833' with 16SXS,210ft.
- <- Plug above CIBP at 5285' from 5285' to 5180' with 8SXS,105ft. <-CIBP Above Perfs at 5285' <-Top Perf at 5335'

- <-CIBP for Mesaverde at 5871'

- <-PBTD at 7911'
- <- Production Casing Shoe at 7936'
- <-TD at 7955'

Sundry Number: 73885 API Well Number: 43047356620000

		FORM 9			
	DEPARTMENT OF NATURAL RESOURGE DIVISION OF OIL, GAS, AND MII		3	5.LEASE ML-470	DESIGNATION AND SERIAL NUMBER: 062
SUNDR	RY NOTICES AND REPORTS	ON	WELLS	6. IF INDI	AN, ALLOTTEE OR TRIBE NAME:
	oposals to drill new wells, significantly reenter plugged wells, or to drill horizon n for such proposals.			7.UNIT or PONDER	r CA AGREEMENT NAME: ROSA
1. TYPE OF WELL Gas Well					NAME and NUMBER: IZA 1023-20
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ON	NSHORE, L.P.			9. API NU 430473	MBER: 856620000
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18tl	h Street, Suite 600, Denver, CO, 8021		NE NUMBER: 720 929-6		and POOL or WILDCAT: AL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0865 FSL 1947 FEL				COUNTY	
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 02 Township: 10.0S Range: 23.0E Merio	dian: \$	S	STATE: UTAH	
11. CHEC	K APPROPRIATE BOXES TO INDICA	TE N	ATURE OF NOTICE, REPOR	RT, OR O	THER DATA
TYPE OF SUBMISSION			TYPE OF ACTION		
	ACIDIZE		ALTER CASING		CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS		CHANGE TUBING		CHANGE WELL NAME
	CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS		CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN DEEPEN	☐ F	RACTURE TREAT		NEW CONSTRUCTION
8/18/2016	OPERATOR CHANGE	√ F	PLUG AND ABANDON		PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME	□ F	RECLAMATION OF WELL SITE		RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL		TEMPORARY ABANDON
_	TUBING REPAIR	\Box	/ENT OR FLARE		WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF		SI TA STATUS EXTENSION		APD EXTENSION
	WILDCAT WELL DETERMINATION		OTHER	OTHE	R:
12. DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly show	all pe	rtinent details including dates, d		!
Kerr-McGee Oil &	Gas Onshore, LP has plugg well. Please see the opera details. Thank you.	jed a	and abandoned the	oi FOF	Accepted by the Utah Division of I, Gas and Mining RECORD ONLY September 01, 2016
NAME (PLEASE PRINT) Candice Barber	PHONE NUME 435 781-9749	BER	TITLE HSE Representative		
SIGNATURE N/A			DATE 8/22/2016		
13/ <i>1</i> 3			U/LL/LUIU		

RECEIVED: Aug. 22, 2016

						KIES RI					
				Opera	ilion S	umma	ary Report	10/0004			
Well: BONANZA 1023-20 Project: LITAL LIINTAL					Spud date: 10/3/2004						
Project: UTAH-UINTAH Site: BON							Rig name no.: MILES 4/4				
Event: ABANDONMENT Start date			1		1000.00		End date: 8/18/2016				
Active datum: GL @5,455.99usft (above Mean Sea Level)			UWI: BC	ONANZA	1023-20						
Date	Time Start-End	Duration (hr)	Phase	Code	Sub Code	P/U	MD from (usft)	Operation			
8/16/2016	7:00 - 7:15	0.25	ABANDP	48	В	Р	•	SAFETY = JSA.			
	7:15 - 8:15	1.00	ABANDP	30	G	Р		ROAD RIG TO LOCATION.			
	8:15 - 9:45	1.50	ABANDP	30	Α	Р		MIRU. FINISH SPOTTING IN ALL EQUIP.			
	9:45 - 11:00	1.25	ABANDP	30	F	Р		SICP & SITP= 50#. BLOW DOWN WELL TO PRODUCTION TANKS. CNTRL TBNG W/ 20BBLS TMAC. CNTRL CSNG W/ 20BBLS TMAC. NDWH. UN-LAND TBNG (GOOD, NOT STUCK). LAND TBNG BACK ON HANGER. NUBOP. R/U FLOOR & TBNG EQUIP. UN-LAND TBNG. RMV HANGER.			
	11:00 - 14:30	3.50	ABANDP	31	I	Р		MIRU SCANNERS POOH WHILE SCANNING 227JTS 2-3/8" J-55 TBNG. L/D ALL TBNG AS SINGLES FOR BETTER INSPECTION. SCAN RESULTS AS FOLLOWS: Y-BND= 86JTS. 2728' R-BND= 141JTS. 4472'			
								RDMO SCANNERS.			
	14:30 - 16:30	2.00	ABANDP	34	I	Р		MIRU WIRELINE. P/U & RIH W/ GR-JB FOR 4-1/2" CSNG TO 5800' GOOD. POOH. P/U & RIH W/ 4-1/2" WF CIBP. SET CIBP @ 5871'. POOH E-LINE. RDMO E-LINE. SWIFN. LOCK RAMS. SDFN. NOTE: RICHARD POWELL W/ UDOGM NOTIFIED OF P&A ACTIVITY AND SAID TO PROCEED AS			
								PLANNED.			
8/17/2016	7:00 - 7:15	0.25	ABANDP	48	В	Р		SAFETY= JSA.			
	7:15 - 9:20	2.08	ABANDP	34	D	Р		SICP= 150#. BLOW DOWN WELL TO FLOWBACK TANK. CNTRL CSG W/ 20BBLS TMAC. MIRU WIRELINE. P/U & RIH W/ DUMP BAILER. SPOT 8SX 15.8# G CMT ON CIBP @ 5871'. 4 WIRELINE RUNS TOTAL. POOH E-LINE. RDMO E-LINE.			
	9:20 - 12:00	2.67	ABANDP	31	G	Р		P/U & RIH W/ 4-1/2" WF CIBP + 166JTS 2-3/8" J-55 TBNG. SET CIBP @ 5285'.			
	12:00 - 12:35	0.58	ABANDP	31	Н	Р		MIRU CMT CREW. BREAK CONV CIRC W/ TMAC. CIRC WELLBORE CLEAN & GAS FREE W/ 80BBLS TMAC.			
	12:35 - 12:50	0.25	ABANDP	52	F	Р		PRESSURE TEST 4-1/2" CSNG & 4-1/2" CIBP GOOD @ 620#. LOST 0# IN 15MIN.			

8/22/2016 1:00:29PM 1

						er: 4 KIES RE	CION	
Well: BONANZA 1023-20 Spud date: 10/3/2004								
Well: BONANZA 1023-20			100170 40			Spud date: 10/		
Project: UTAH-UINTAH Site: BO			Site: BON	NANZA 10	023-20			Rig name no.: MILES 4/4
l l			Start date			1000.00		End date: 8/18/2016
ctive datum: (evel)	GL @5,455.99usft (abo	ove Mean Sea	a 	OWI: BO	JNANZA -	1023-20		
Date	Time Start-End	Duration (hr)	Phase	Code	Sub Code	P/U	MD from (usft)	Operation
	12:50 - 14:05	1.25	ABANDP	51	D	P		POOH W/ TBNG WHILE PUMPING CMT PLUGS. ALL CMT PUMPED @ 15.8# AND IS G CMT. PUMP CMT PLUGS AS FOLLOWS: #1. CIBP @ 5285'. PUMP 2.6BBL FRESH WATER. PUMP 10SX CMT. DISPLACE W/ 1BBL FRESH WATER & 18.9BBLS TMAC. PUH TBNG. #2. EOT @ 4043'. PUMP 2.6BBL FRESH WATER. PUMP 16SX CMT. DISPLACE W/ 1BBL FRESH WATER & 13.7BBLS TMAC. PUH TBNG. #3. EOT @ 3305'. PUMP 2.6BBL FRESH WATER. PUMP 60SX CMT. DISPLACE W/ 1BBL FRESH WATER & 8.4BBLS TMAC. PUH TBNG. #4. EOT @ 1940'. PUMP 2.6BBL FRESH WATER. PUMP 10SX CMT. DISPLACE W/ 1BBL FRESH WATER & 5.9BBLS TMAC. PUH TBNG. L/D EXCESS NOT NEEDED FOR SQZ. JOB. POOH REM 31JTS NEEDED FOR SQZ.
	14:05 - 14:40	0.58	ABANDP	34	Н	Р		MIRU WIRELINE. P/U & RIH W/ 4SPF X 1' SQZ GUN. PERF 4-1/2" PRODUCTION CSNG @ 1080'. POOH E-LINE. TRY TO EST INJECTION RATE BUT COULD NOT INJECT @ 500#. ALSO WOULD NOT PRESSURE TEST. LOSING 100# IN 1MIN. RDMO WIRELINE.
	14:40 - 17:30	2.83	ABANDP	51	D	Р		DECIDE TO PUMP BALANCED PLUG ACROSS PERF HOLES. P/U & RIH W/ N.C. & 35JTS 2-3/8" J-55 TBNG. EOT @ 1137'. R/U CMT CREW. BREAK CONV CIRC. PUMP 2.6BBL FRESH WATER. PUMP 29SX CMT. DISPLACE W/ 1.9 BBLS TMAC. POOH WHILE L/D 11JTS TBNG. REV CIRC W/ 6BBLS TMAC UNTIL CLEAN. L/D 3 MORE JTS TBNG. SWIFN. SDFN. NOTE: RICHARD POWELL W/ UDOGM ON LOCATION
8/18/2016	7:00 - 7:15	0.25	ABANDP	48	В	Р		TO WITNESS P&A. SAFETY = JSA.
0/10/2010	7:15 - 8:00	0.25	ABANDP	31	I	P		0# ON WELL. RIH 3JTS TBNG & TAG CMT @ 781'.
								POOH WHILE L/D ALL TBNG.

8/22/2016 1:00:29PM 2

8:00 - 9:30 1.50 ABANDP 30 C P

R/D FLOOR & TBNG EQUIP. NDBOP. RDMOL.

Sundry	Number: '	73885	APT We	<u>, 11 </u>	Iumbe	r: 43	3047356	620000	
				U	S ROC	KIES RE	GION		
				Opera	tion S	Summai	y Report		
Well: BONANZA 1023-2O Spud date: 10/3/2004							/3/2004		
Project: UTAH-U	INTAH		Site: BON	IANZA 10	023-20			Rig name no.: MILES 4/4	
Event: ABANDO	NMENT		Start date	: 7/5/2016				End date: 8/18/2016	
Active datum: GL	_ @5,455.99usft (abo	ve Mean Sea	•	UWI: BO	UWI: BONANZA 1023-20				
Level)									
Date	Time Start-End	Duration (hr)	Phase	Code	Sub Code	P/U	MD from (usft)	Operation	
	9:30 - 11:30	2.00	ABANDP	51	D	P		MIRU ROUSTABOUT CREW. EXPOSE WELLHEAD. CUT & LOWER WELLHEAD. RIH IN 4-1/2" CSNG W/ 100' 1" TBNG. PUMP 10SX 15.8# CMT TO SURFACE & STAYED FULL. SURFACE CSNG FULL OF DRILLING MUD. RIH W/ 1" TBNG DOWN SURFACE CSNG TO 50'. WASH DOWN DRILLING MUD & DISPLACE W/ 40SX 15.8# G CMT. CMT STAYED FULL. CAP WELL. BACKFILL WELLHEAD. P&A COMPLETE.	
								NO STATE REP ON LOCATION. RICHARD POWELL (UDOGM) SAID TO PROCEED AS PLANNED W/ P&A WHILE ON LOCATION THE PREVIOUS DAY. WELLHEAD COORDINATES:	
								LAT: 39.97305 LONG: -109.291797	

8/22/2016 1:00:29PM 3